

OCULUS LED 12850LM 840 IP23 I KL. AW 3H 75D SP10KV 72W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	964381
Nominal power [W]:	72
Luminous flux [lm]*:	12850
Colour temperature [K]:	4000
Electrical protection class:	I
Energy efficiency class:	B
Material of the body:	powder coated aluminium
Diffuser material:	PC
Beam angle [°]:	75
Working temperature [°C]:	from 0 to +25

CHARACTERISTICS

OCULUS LED is a HIGH-BAY luminaire from the NEXT GEN product line, constituting a new generation of luminaires dedicated to LED technology. The designed-from-scratch body – made of die-cast aluminium and powder coated – uses natural conduction and convection processes, which have a positive effect on luminaire's heat management. The shape of the body with an integrated, effective heat sink and high-quality materials ensure maximum heat dissipation from the LED module. The driver's external compartment, separated from the body, guarantees optimal thermal working conditions for the power supply system. This enables the luminaire to work in an ambient temperature of max 60°C. LEDs from a reputable manufacturer and new LED modules enable very high luminous efficiency: max 176 lm/W. This guarantees that the required lighting level and significant energy savings are achieved. The diffuser and optical system are composed of precise linear lenses made of polycarbonate (PC). There are 3 dedicated ranges of light distribution available: 55°, 75°, 105°. GLASS version with tempered glass (without lenses) and 105° distribution is also available.

Standard equipped with a 0.3 m long H07RN-F cable terminated with an additional male and female connector, which makes the assembly easier and more convenient.

Available version with radio motion sensor:

- allowing additional savings in electricity consumption
- convenient change of parameters by remote control (to be purchased separately).

Its design is adapted for suspended mounting and surface mounting (ceiling and wall) requiring the use of additional accessories.

APPLICATION

The luminaire is intended for suspended mounting (using chains, wires, etc.) both indoors and outdoors. It will prove perfect for manufacturing plants and halls as well as large-format warehouses and logistics centres.

OCULUS LED 12850LM 840 IP23 I KL. AW 3H 75D SP10KV 72W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	72	Mounting version:	suspended
Index:	964381	Cable length [m]:	0.30
Colour temperature [K]:	4000	Dimensions of single box [mm]:	175/400/400
Luminous flux [lm]:	12850	Net weight [kg]:	5.650
Light source:	LED module	Category type:	high-bay and low-bay
Diffuser material:	PC	AC voltage range [V]:	198-264
Rated power of the luminaire [W]:	76	DC voltage range [V]:	176-280
Beam angle [°]:	75	LED lifespan L70B50 [h]:	196000
Supply voltage [V]:	220-240	LED lifespan L80B20 [h]:	123000
Frequency [Hz]:	50 - 60	LED lifespan L90B10 [h]:	60000
Working temperature [°C]:	from 0 to +25	Accessories included:	Eye bolt
Luminous efficacy [lm/W]:	170	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Energy efficiency class:	B	Charging time [h:min]:	1
Electrical protection class:	I	Battery life [h:min]:	3
Colour rendering index:	>80	Battery:	NiMh
SDCM:	≤ 3	Battery capacity [mAh]:	4
Power factor:	0.95	Emergency lighting [h]:	3
Surge protection [kV]:	4	Autotest:	yes
Diffuser type:	transparent	Operating mode:	M
Diffuser colour:	transparent	ETIM class:	EC001716
Optics material:	PC	The number of implement units:	1
Optics:	lens	Warranty [years]:	2 / 0.5 (bateria)
Material of the body:	powder coated aluminium	ENEC Certificate:	PL BBJ/005/2021/M1
Colour of the body:	grey	CE certificate:	153/2023
Dimensions (H/W/T/S) [mm]:	595/371	PZH certificate:	B-BK-60212-0481/21
Impact resistance:	IK09	HACCP:	852/2004
Ingress protection:	IP23	Manual:	Download PDF

OCULUS LED 12850LM 840 IP23 I KL. AW 3H 75D SP10KV 72W


DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
964244	OCULUS LED - RCR motion sensor
964886	OCULUS LED - universal handle-lack of compatibility with Dali version 294W
964893	OCULUS LED - surface mounting handle-lack of compatibility with Dali version 294W
964862	OCULUS LED - protective grid
963674	OCULUS LED - RCR / PIR DALI motion sensor
WSEL438	Remote control for motion sensor HD01R
WSEL415	WSEL415 Remote control for - PIR sensor




OCULUS LED - RCR motion sensor (964244)



OCULUS LED - universal handle-lack of compatibility with Dali version 294W (964886)




OCULUS LED - surface mounting handle-lack of compatibility with Dali version 294W (964893)




OCULUS LED - protective grid (964862)



OCULUS LED - RCR / PIR DALI motion sensor (963674)



Remote control for motion sensor HD01R (WSEL438)



WSEL415 Remote control for - PIR sensor (WSEL415)