



FLAT POLYMERO

311943.002.1 | Ceiling and wall luminaires



Ceiling and wall luminaires
4051859099178
D 300, H 100

Ceiling mounting, Wall (surface)
white



Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: patented push system. Suitable for Ceiling mounting, Wall (surface).

Product specifications

Diameter D	300 mm
Height H	100 mm
Weight	1.05 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux	1150 lm
System power	12 W
System efficiency	96 lm/W
Glare evaluation UGR (4H 8H)	19,6
Beam angle	down 118° up 180°
Rated life	50000 h (L80/B10)
Colour rendering index (CRI)	83
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	Phase cut-off/cut-on
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	136
Luminaires on B16A fuse	218
Luminaires on C10A fuse	136
Luminaires on C16A fuse	218
Inrush current / Inrush current duration	0.15 A / 300 µs
CIE Flux Code / CEN Flux Code	41 70 89 86 100
Type of protection	IP 40
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK03
Ambient temperature	25 °C
Conformity mark	CE, EAC

Spareparts



08-311623.002
Replacement diffuser