PRODUCT DATASHEET
SMART+ BT NIGHTLIGHT PLUG EU

SMART+ NIGHTLIGHT Plug | Nightlight integrated plug with smart socket to control non smart devices with Bluetooth technology

Areas of application

– Wherever non-smart devices need to be integrated into compatible smart home systems
– Nightlight as an orientation light or safety light for children's rooms, stairs, or bedrooms

Product benefits

– Integrates conventional electric equipment into compatible smart home systems
– Nightlight as an orientation light or safety light at night or in dark area
– Simple connection of electric devices via standard socket
– Enables switching of conventional light sources and other electric devices

Product features

– Controllable via LEDVANCE SMART+ App (with minimum Android 6.0 or iOS 11.0)
– Control via voice available: Apple Homekit, Google Assistant, Amazon Alexa
– For full functionality with control via Apple Home App connection to Apple TV (with tvOS 10 or later) or iPad (with iOS 10 or later) required
– High switching power: up to 3,680 W / 16 A
– Network protocol: Bluetooth
– Nightlight integrated with warm white, not dimmable
– Scheduling

TECHNICAL DATA

Electrical data

Nominal voltage	230 V
Mains frequency	50 Hz

Dimensions & Weight

Product weight	120.00 g
Length	60 mm
Width	60 mm
Height	84 mm

Lifespan

Number of switching cycles	100000

Colors & materials

Product color	White
Body material	Plastic

Temperatures & operating conditions

Ambient temperature range	-10...+35 °C

Capabilities

Compatible smart home technology	Amazon Alexa / Google Assistant / Apple HomeKit

Certificates & Standards

Protection class	I
Type of protection	IP20

EQUIPMENT / ACCESSORIES

– For control via LEDVANCE SMART + App Android smartphone (with Android 6.0 and later) required

– For control via Apple Home App iPhone (with iOS 10 or later), iPad (with iOS 10 or later) , Apple TV (with tvOS 10 or later) or Apple Watch (with watchOS 2 or later) required

Safety advice

– Disconnect devices which generate heat from the mains, i.e. from the SMART+ Plug, after use in order to avoid them being accidentally switched on.
– Very high capacitive and inductive loads may in some cases lead to destruction of the device or reduction in the number of switching cycles.
– Do not use the SMART+ Plug in conjunction with medical equipment.
– To be connected to an automatic circuit breaker (max. 16 A).

DOWNLOAD DATA

	Documents and certificates
PDF	Installation guide
PDF	Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075571013	Folding box 1	61 mm x 96 mm x 154 mm	188.00 g	0.90 dm³
4058075571020	Shipping box 4	211 mm x 167 mm x 141 mm	886.00 g	4.97 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.