

PHOBOS LED 6300LM 840 IP20 I KL. OPAL (53W) 500MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	462245
Ingress protection:	IP20
Impact resistance:	IK08
Nominal power [W]:	53
Luminous flux [lm]*:	6300
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	powder coated steel
Diffuser material:	PS

CHARACTERISTICS

Surface-mounted, round LED fitting with very high diffuser diameter, high luminous flux and even light distribution. Includes an integrated energy-saving light source LED. Galvanized steel base, powder-coated white; light, white acrylic diffuser made using thermoforming method. Simple pawl-based mounting system does not require any additional tools and safeguards the diffuser against uncontrolled fall. The luminaire may be used to replace standard four-lamp fittings in irregular shaped rooms. Designed to work with a radio motion sensor or the DALI system.

APPLICATION

Surface mounted fitting intended for indoor use characterized by even light distribution and good surface lighting. Particularly suitable as a general light source in representative rooms and passageways. Thanks to exceptional lighting parameters, possible integration with the DALI system and decorative qualities, the product will surely prove its worth in large conference halls.

PHOBOS LED 6300LM 840 IP20 I KL. OPAL (53W) 500MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	53	Working temperature [°C]:	from -25 to +35
Light source:	LED module	Net weight [kg]:	3.700
Colour temperature [K]:	4000	Warranty [years]:	5
Luminous flux [lm]:	6300	CE certificate:	389/2023
Rated power of the luminaire [W]:	55	Index:	462245
Supply voltage [V]:	220-240	EAN:	5905963462245
Diffuser type:	OPAL	Category type:	bulkheads
Frequency [Hz]:	50 - 60	LED lifespan L70B50 [h]:	90000
Luminous efficacy [lm/W]:	115	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Energy efficiency class:	E	Diffuser colour:	white
Electrical protection class:	I	Optics material:	PC
Colour rendering index:	>80	Optics:	matrix lens
SDCM:	≤ 3	Mounting dimensions [mm]:	ø418
Power factor:	0.96	Dimensions of single box [mm]:	515/515/115
Diffuser material:	PS	Version:	LV
Material of the body:	powder coated steel	Light distribution type:	lambertian
Colour of the body:	white	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	ø500/110	Warranty [years]:	5
Impact resistance:	IK08	Plik LDT:	Download
Ingress protection:	IP20		
Mounting version:	surface		

LIGHT CURVES

