




Pole top luminaires  
4051859678854  
D 187, H 572

Pole mounting  
silver, matt (approx. RAL 9006)



Pole-top luminaire with classic design and modern LED technology. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. With stainless steel screws. With membrane valve as a standard to avoid condensed water. Diffuser: glass, transparent. Multi-chip LED with high-performance refractor optics. Asymmetrical light distribution. Pole attachment for 76 mm spigot. With stainless steel screws. Elegant-looking power supply via delicate steel cables between converter and LED. Converter integrated in the luminaire head. Pre-assembled connection cable 2 x 0.75 mm<sup>2</sup>, length 6 m. Please order reducer adapter for pole clamp D 60 mm separately. Order the top roof separately as an accessory for the classic lantern shape.

Product specifications

Diameter D	187 mm
Height H	572 mm
Weight	6.1 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux	1600 lm
System power	14 W
System efficiency	114 lm/W
Glare evaluation UGR (4H 8H)	32,3
Beam angle	79°/64°/79°/51°
Rated life	100000 h (L80/B10)
Colour rendering index (CRI)	70
Colour tolerance	5
Photobiological safety according to EN 62471	Risk group 2
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	18
Luminaires on B16A fuse	28
Inrush current / Inrush current duration	26 A / 180 µs
CIE Flux Code / CEN Flux Code	21 51 89 100 100
Type of protection	IP 66
Protection class	II
Filament test	960°C - 30 seconds
Impact resistance	IK06
Ambient temperature	-20 °C ... + 40 °C
Conformity mark	CE, EAC

Accessories



982752.004  
Top roof



982762.000  
Reducing adapter Ø 60 mm