


SERIE TO500 (SERRAVALLE) PER RAIL TH35			
Descrizione	Materiali	Dimensioni	Caratteristiche
TO500/01	PA66	47x10x10	10mm ²
TO500/02	PA66	47x10x10	16mm ²
TO500/03	PA66	47x10x10	25mm ²
TO500/04	PA66	47x10x10	35mm ²
TO500/05	PA66	47x10x10	50mm ²
TO500/06	PA66	47x10x10	70mm ²
TO500/07	PA66	47x10x10	95mm ²
TO500/08	PA66	47x10x10	120mm ²
TO500/09	PA66	47x10x10	150mm ²
TO500/10	PA66	47x10x10	190mm ²

Screw

terminal block 10mm², 1-level, earth connection, for TH35 rail

Series	TE
Code	TO500
Type	TE.10/O
HS code	85369010
Colour	Yellow-green
TECHNICAL FEATURES	
Function/Type	Earth terminal blocks
Rated cross-section	10 mm ²
Connecting capacity	
Flexible wire	0.5-10 mm ²
Rigid wire	0.5-16 mm ²
Wire with ferrule - ferrule type	10 mm ² – WP100/21
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	–
Maximum current (rated cross-section)	–
Caliber	B6
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	–
Section (min-max)	20-8 (AWG)
Tightening torque value (UL)	13.3 lb.in
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	–
Maximum current (rated cross-section)	57 A
Operating temperature Min/Max	-40 °C / +110 °C
Rated impulse withstand voltage / pollution degree	8 kV / 3
Insulation stripping length	13 mm
Tightening torque value (nom. / max.)	1.2 / 1.9 Nm
Width (pitch)	10 mm
Length	47 mm
Height mounted on TH35-7.5/TH35-15/G32	55 / 63 / – mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	–
Green	–
Thickness	–
Cross-connection	
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S) – CNU/10/61 (cod. NU1061S)
Single marking tag for pitch insertion	–
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	PR/DIN/...
APPROVALS AND MARKINGS	



DESCRIZIONE DEL PRODOTTO

TE.10/O Screw terminal block 10mm², 1-level, earth connection, for TH35 rail