

PRODUCT DATASHEET

L 36 W/4000 K

Basic T8 | Tubular fluorescent lamps 26 mm, with G13 bases



TECHNICAL DATA

Electrical data

Nominal wattage	36 W
Construction wattage	36.00 W
Nominal voltage	230 V
Nominal current	0.43 A
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Photometrical data

Luminous flux	2850 lm
Luminous efficacy	79 lm/W
Color temperature	4000 K
Light color	40
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Dimensions & Weight

Overall length	1200.00 mm
Length with base excl. base pins/connection	1200 mm
Diameter	26.00 mm
Tube diameter	26 mm
Product weight	147.00 g

Lifespan

Lifespan	13000 h
Service life	5000 h

Additional product data

Base (standard designation)	G13
Mercury content	8.0 mg

Country-specific categorizations

Order reference	L 36W/640
-----------------	-----------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13
Length	1200.00 mm
Height	26.00 mm

Width	26.00 mm
-------	----------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899352810	Sleeve 1	1,210 mm x 28 mm x 27 mm	167.00 g	0.91 dm ³
4052899352827	Shipping box 25	1,234 mm x 150 mm x 155 mm	4510.00 g	28.69 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.