

PRODUCT DATASHEET

Renovation Lamp Classic A75 Terminal Block 10W 840 Single Pack

RENOVATION LAMPS WITH TERMINAL BLOCK | LED lamp with a terminal block for direct connection to the ceiling or wall at construction sites or for moving



Areas of application

- New construction sites or apartments and houses for temporary light
- Practical temporary light for indoor ceiling or wall installation
- For indoor use only

Product benefits

- Ideal light for construction sites, renovations, or moving
- Can be easily and quickly fitted
- Offered in a closed box, the integrated terminal block ensures safe installation on the wall or ceiling

Product features

- The lamp has an integrated power cable, including the terminal block
- The lamp can be directly connected to AC 220-240V without a socket
- A strong lumen output with 1050 lm at 4000K provides bright and energy efficient light
- The light source is not replaceable



TECHNICAL DATA

Electrical data

| | |
|------------------------|-------------|
| Nominal wattage | 10.00 W |
| Nominal voltage | 220...240 V |
| Nominal current | 70.000 mA |
| Type of current | AC |
| Inrush current | 6.4 A |
| Operating frequency | 50/60 Hz |
| Mains frequency | 50/60 Hz |
| Power factor λ | > 0.5 |


Photometrical data

| | |
|--------------------------------------|---------------------|
| Luminous flux | 1055 lm |
| Luminous efficacy | 105 lm/W |
| Light color (designation) | Cool white |
| Color temperature | 4000 K |
| Color rendering index Ra | > 80 |
| Light color | 840 |
| Standard deviation of color matching | ≤6 sdc _m |
| Flickering metric (Pst LM) | 1 |
| Stroboscope effect metric (SVM) | 0.4 |

Light technical data

| | |
|------------|-------|
| Beam angle | 200 ° |
|------------|-------|

Dimensions & Weight



| | |
|----------|----------|
| Diameter | 60.00 mm |
|----------|----------|

| | |
|----------------|---------|
| Product weight | 55.00 g |
|----------------|---------|

Temperatures & operating conditions

| | |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
|---------------------------|--------------|

Lifespan

| | |
|---------------------------|---------|
| Lifespan L70/B50 at 25 °C | 15000 h |
|---------------------------|---------|

Additional product data

| | |
|-----------------|------------------------------|
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Product remark | Available from February 2025 |

Capabilities

| | |
|----------|----|
| Dimmable | No |
|----------|----|

Certificates & Standards

| | |
|--|-----------------|
| Type of protection | IP20 |
| Standards | CE / EAC / UKCA |
| Photobiological safety group acc. to EN62778 | RG1 |

Country-specific categorizations

| | |
|-----------------|-----------------|
| Order reference | RENOVATION CLA7 |
|-----------------|-----------------|

LOGISTICAL DATA

| | |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

Energy labelling regulation data acc EU 2019/2015

| | |
|--------|-----------|
| Length | 98.00 mm |
| Height | 291.00 mm |
| Width | 60.00 mm |




EQUIPMENT / ACCESSORIES

- Integrated 13-cm long power cable and the terminal block in closed box

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|--|---------------|
|  | User instruction / safety instructions | RENOV Lamp UI |
|  | Declarations of conformity | Luminares |
|  | Declarations of conformity UKCA | Luminaries |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4099854421457 | Folding box 1 | 62 mm x 62 mm x 162 mm | 54.00 g | 0.62 dm ³ |
| 4099854421464 | Shipping box 10 | 338 mm x 143 mm x 129 mm | 748.00 g | 6.24 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.