

NECTRA LED PLUS 121MM 860LM 830 IP44 AW 3H AT OPAL WHITE (9W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	517754
Ingress protection:	IP44
Nominal power [W]:	9
Luminous flux [lm]*:	860
Colour temperature [K]:	3000
Colour rendering index:	>80
Energy efficiency class:	F
Material of the body:	PC, aluminium
Colour of the body:	white
Diffuser material:	PMMA

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Its distinctive features are low profile, light weight and very easy and fast installation. Design for both solid and modular ceilings.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

NECTRA LED PLUS 121MM 860LM 830 IP44 AW 3H AT OPAL WHITE (9W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	9
Light source:	LED module
Colour temperature [K]:	3000
Luminous flux [lm]:	860
Rated power of the luminaire [W]:	10
Diffuser type:	OPAL
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Emergency lighting [h]:	3
Autotest:	yes
Operating mode:	M
Luminous efficacy [lm/W]:	86
Dimensions (H/W/T/S) [mm]:	ø121/67
Energy efficiency class:	F
Electrical protection class:	I
Colour rendering index:	>80
SDCM:	≤ 3
Power factor:	0.80
Charging time [h:min]:	24:00
Beam angle [°]:	88
Battery:	Ni-Mh
Diffuser material:	PMMA
Optics material:	aluminium

Optics:	reflector
Material of the body:	PC, aluminium
Colour of the body:	white
Ring material:	PC
Ring colour:	white
Mounting dimensions [mm]:	ø100
Impact resistance:	IK08
Ingress protection:	IP44
Mounting version:	recessed
Working temperature [°C]:	from 0 to +35
Net weight [kg]:	0.600
CE certificate:	340/2023
Warranty [years]:	2 / 0.5 (bateria)
Index:	517754
EAN:	5905963517754
Category type:	downlights
Luminaire rated power P_{min} [W]:	10.80
AC voltage range [V]:	198 - 264
LED lifespan L70B50 [h]:	80000
LED lifespan L80B20 [h]:	55000
LED lifespan L90B10 [h]:	30000
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	2 / 0.5 (battery)
Manual:	Download PDF

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 340/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl