


# DEECOS S mini track-in

742256.004.1.76 | Surface mounted projector



Surface mounted projectors  
4051859813774  
D 87, H 135

Track on ceiling, Wall track  
silver



LED surface-mounted projector in modern design with no visible cooling ribs. Housing: die-cast aluminium, powder-coated. Rotation range: 356°. Swivel range: 90°. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. Best colour rendering index Ra>90. With adapter for RZB 3-circuit DALI tracks. Suitable for Track on ceiling, Wall track. Track-in driver integrated into the adapter. High quality converter without flickering and stroboscopic effect. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring.

### Product specifications

|                                              |                          |
|----------------------------------------------|--------------------------|
| Diameter D                                   | 87 mm                    |
| Height H                                     | 135 mm                   |
| Weight                                       | 0.62 kg                  |
| Light source                                 | LED                      |
| Colour temperature                           | 4000 K                   |
| Rated luminous flux                          | 2450 lm                  |
| System power                                 | 20 W                     |
| System efficiency                            | 123 lm/W                 |
| Glare evaluation UGR (4H 8H)                 | 25,7                     |
| Beam angle                                   | 72°                      |
| Rated life                                   | 50000 h (L90/B10)        |
| Colour rendering index (CRI)                 | 92                       |
| Colour tolerance                             | 2                        |
| Photobiological safety according to EN 62471 | Risk group 1             |
| Driver                                       | Converter, dimmable      |
| Control                                      | DALI                     |
| Voltage                                      | 220 - 240 V / 50 - 60 Hz |
| Luminaires on B16A fuse                      | 27                       |
| Luminaires on C16A fuse                      | 44                       |
| Inrush current / Inrush current duration     | 18 A / 2 µs              |
| CIE Flux Code / CEN Flux Code                | 80 99 100 100 100        |
| Type of protection                           | IP 20                    |
| Protection class                             | II                       |
| Filament test                                | 650°C - 30 seconds       |
| Impact resistance                            | IK06                     |
| Ambient temperature                          | 25 °C                    |
| Conformity mark                              | CE, EAC                  |

### Accessories




982370.000  
Diffuser, transparent



982370.010  
Diffuser, satinated

# DEECOS S mini track-in

742256.004.1.76 | Surface mounted projector



982371.003  
Anti-glare honeycomb louvre



982369.013  
Medium lens



982421.002  
White plastic ring for lens.



982368.013  
Reflector medium



982369.033  
Wide flood lens



982419.002  
White plastic ring for reflector.




982647.002  
Decorative glass opal matt




982369.003  
Spot lens



982369.023  
Flood lens



982368.003  
Reflector spot



982368.023  
Reflector flood



982369.043  
Oval corridor lens



982368.033  
Reflector wide flood



982648.002  
Decorative glass opal matt