## MINGATA INTERNATIONAL mini


612306.0031.76 | Pole luminaires





Outdoor luminaires and pole top luminaires 4051859698043 L 530, B 270, H 100

Pole mounting anthracite metallic (DB703)



Functional pole-side and pole-top luminaire in a modern design. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. Pole-top fixing with integrated cable routing and stainless steel screws. With membrane valve as a standard to avoid condensed water. Tilt angle can be adjusted and locked in 5 degree steps featuring angular scale. Cover clear single-pane toughened glass. Asymmetrical light distribution. Luminaires for pole top Ø 76 mm (with optional adapter sleeve, also suitable for pole top Ø 60 mm). Tool-free maintenance / replacement by Eccentric-Lock system with disconnect plug and Hybrid-Lock-System. DALI control gear with integrated surge protection up to 10 kV. With NFC programming interface. Constant light output (CLO). Luminaire built-in 10kV surge protector (L,N,Earth). Preassembled connection cable 3 x 1.5 mm² (H07RN-F), length 12.5 m. Please order reducer adapter for pole clamp D 60 mm separately.

#### **Product specifications**

1 Todact specifications	
Length L	530 mm
Width B	270 mm
Height H	100 mm
Weight	5.4 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux	5800 lm
System power	45 W
System efficiency	129 lm/W
Glare evaluation UGR (4H 8H)	36,4
Beam angle	68°/66°/68°/0°
Rated life	100000 h (L80/B50)
Colour rendering index (CRI)	70
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	8
Luminaires on B16A fuse	12
Inrush current / Inrush current duration	54 A / 180 μs
CIE Flux Code / CEN Flux Code	28 68 98 100 100
Type of protection	IP 66
Protection class	<u> </u>
Filament test	960°C - 30 seconds
Impact resistance	IK08
Ambient temperature	-20 °C + 50 °C
Conformity mark	CE

# MINGATA INTERNATIONAL mini

### 612306.0031.76 | Pole luminaires



#### **Accessories**



982562.000 Reducing adapter Ø 60 mm



982589.000 Pole bracket for 3 luminaires, uncoated



982591.000 Wall bracket, uncoated



982588.000 Pole bracket for 2 luminaires, uncoated



982590.000 Pole bracket for 4 luminaires, uncoated



61199.009 Fuse box