



LESS IS MORE vario

312689.004.1 | Linear systems



Ceiling and wall luminaires
4051859972679
L 1971, B 110, H 88

Ceiling mounting
silver, matt (approx. RAL 9006)



Linear ceiling and wall luminaire for aesthetically sophisticated lighting. Housing: extruded aluminium profile, powder-coated. End cap aluminium powder-coated, without visible screws. Diffuser made of non-yellowing plastic (PMMA) microprismatic. Specially matched 2-component optical system for glare-free light at the workstation (suitable for use in environments with computer screens in accordance with EN 12464-1). Suitable for Ceiling mounting. LED unit with integrated converter interchangeable and removable. Suitable for through-wiring.

Product specifications

Length L	1971 mm
Width B	110 mm
Height H	88 mm
Weight	6.797 kg
Light source	LED
Colour temperature	4000 K
Rated luminous flux	3950 lm
System power	29 W
System efficiency	136 lm/W
Glare evaluation UGR (4H 8H)	18,2
Beam angle	81°/82°
Rated life	50000 h (L90/B50)
Colour rendering index (CRI)	80
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	15
Luminaires on B16A fuse	24
Luminaires on C10A fuse	24
Luminaires on C16A fuse	40
Inrush current / Inrush current duration	13 A / 270 µs
CIE Flux Code / CEN Flux Code	67 91 98 99 100
Type of protection	IP 20
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK03
Ambient temperature	-20 °C ... + 35 °C
Conformity mark	CE, EAC