

PRODUCT DATASHEET

LS AY PFM -CSD-P2-COB

Connectors for COB LED Strips Performance Class | Connectors for COB LED Strips Performance Class



Areas of application

- General indoor illumination

Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

TECHNICAL DATA

Electrical data

Nominal voltage	24 V
Nominal current	2.5 A

Dimensions & Weight

Length	16.0 mm
Width	10.0 mm
Height	4.0 mm
Cable cross-section, input side	0.5 mm ²
Product weight	0.52 g

Colors & materials

Product color	Transparent
---------------	-------------

Temperatures & operating conditions

Ambient temperature range	-30...+85 °C
Temperature range in operation	-30...+85 °C


Certificates & Standards

Type of protection	IP00
--------------------	------

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

DOWNLOAD DATA

Tender texts	Document name
 Tender documents	Connectors for COB LED Strips Performance Class CSD P2 COB-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075654112	BAG 2	50 mm x 30 mm x 4 mm	4.00 g	0.01 dm ³
4058075654129	Shipping box 400	353 mm x 147 mm x 200 mm	993.00 g	10.38 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.