

PRODUCT DATASHEET

L 58W 830

LUMILUX® T8 | Tubular fluorescent lamps 26 mm, with G13 bases



Areas of application

- Public buildings
- Office lighting
- Industry
- Shops
- Supermarkets and department stores
- Street lighting
- Outdoor applications only in suitable luminaires

Product benefits

- Proven lamp technology

Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable

TECHNICAL DATA

Electrical data

Nominal wattage	58 W
Construction wattage	58.00 W
Nominal voltage	220 V

Photometrical data

Luminous flux	5200 lm
Luminous efficacy	89 lm/W
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	> 80
Light color	830

Dimensions & Weight

Overall length	1500.00 mm
Diameter	26.00 mm
Product weight	184.00 g

Additional product data

Base (standard designation)	G13
Mercury content	3.0 mg
Design / version	Frosted

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Energy efficiency class	A
Energy consumption	68.00 kWh/1000h

Country-specific categorizations

Order reference	L 58W/830
-----------------	-----------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13
Length	1500.00 mm

Height	26.00 mm
Width	26.00 mm
EPREL ID	546345
Model number	AC34132

Safety advice

– In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075692893	Sleeve 1	1,515 mm x 28 mm x 27 mm	208.00 g	1.15 dm ³
4058075692909	Shipping box 25	1,532 mm x 150 mm x 145 mm	5594.00 g	33.32 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.