

# RQ 220 LED P 2400LM 840 IP65/IP20 II CL. PRM 19W

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	979231
Ingress protection:	IP65/IP20
Luminous flux [lm]*:	2400
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	D
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	PRM

## CHARACTERISTICS

RQ 200 LED P is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

## APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

The lamp is especially recommended for office spaces, spacious corridors and public spaces.

# RQ 220 LED P 2400LM 840 IP65/IP20 II CL. PRM 19W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	979231	Dimensions (H/W/T/S) [mm]:	221/221/51
EAN:	5905963979231	Mounting dimensions [mm]:	200
Light source:	LED module	Impact resistance:	IK07
Rated power of the luminaire [W]:	19	Ingress protection:	IP65/IP20
Supply voltage [V]:	220-240	Mounting version:	recessed
Frequency [Hz]:	50-60	Working temperature [°C]:	from 0 to +35
Luminous flux [lm]:	2400	Net weight [kg]:	0.330
Luminous efficacy [lm/W]:	127	Warranty [years]:	5
Energy efficiency class:	D	Category type:	downlights
Electrical protection class:	II	LED lifespan L80B20 [h]:	58000
Colour temperature [K]:	4000	CE certificate:	<a href="#">299/2023</a>
Colour rendering index:	>80	Manual:	<a href="#">Manual</a>
Beam angle [°]:	115	Plik LDT:	<a href="#">Download</a>
Diffuser material:	PC		
Diffuser type:	PRM		
Material of the body:	ABS		
Colour of the body:	white		

Card creation date: 17 March 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 299/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)