


Pendant luminaires
4051859234012
L 1512, B 28, H 38

pendant
traffic white, matt (RAL 9016)



Pendant luminaire with slim design. Housing: extruded aluminium profile, powder-coated. End cap aluminium powder-coated. High polish aluminium micro grid. Perfect for office areas ($UGR \leq 19$) and environments with computer screens in accordance with EN 12464-1. Direct 60%, indirect 40% light emission. Suitable for pendant. 2-point steel cable suspension, steplessly adjustable. Special lengths available on request. External driver with connecting cable.

Product specifications

Length L	1512 mm
Width B	28 mm
Height H	38 mm
Suspension length LP	100-1500 mm
Weight	1.65 kg
Light source	LED
Colour temperature	#4000 K #4000 K
Rated luminous flux	2800 lm
System power	33 W
System efficiency	85 lm/W
Glare evaluation UGR (4H 8H)	12,5
Beam angle	down 66°/45° up 77°/102°
Rated life	60000 h (L80/B10)
Colour rendering index (CRI)	82
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	13
Luminaires on B16A fuse	21
Luminaires on C10A fuse	22
Luminaires on C16A fuse	35
Inrush current / Inrush current duration	21 A / 275 µs
CIE Flux Code / CEN Flux Code	90 99 100 54 100
Type of protection	IP 20
Protection class	II
Filament test	650 °C
Impact resistance	IK00
Ambient temperature	-25 °C ... + 25 °C
Safety marks	Do not cover the recessed luminaire!
Conformity mark	CE, EAC