

**MINIDISC REMOTE  
INDICAT  
ERI-10  
Instruction Sheet  
R10265GB0**

## **Schneider Electric Fire & Security Oy**

Sokerilinnantie 11 C  
FI-02600 Espoo, Finland  
Tel: +358 10 446 511  
Website: [www.se.com](http://www.se.com)  
Document number: R10265GB0  
Published: 18.05.2022

© 2022 – Schneider Electric. All Rights Reserved. This information is only to be used as guidance. Subject to changes and errors.

# Contents

<b>1</b>	<b>MINIDISC REMOTE INDICAT ERI-10.....</b>	<b>4</b>
1.1	Technical data.....	4

# 1 MINIDISC REMOTE INDICAT ERI-10

The MINIDISC REMOTE INDICAT ERI-10 (FFS06720601) is a lightweight compact indicator for use in fire protection systems.

The indicator may be used in all installations incorporating Schneider Electric detectors, which include the Intellia and Essentia series.

The MiniDisc Remote Indicator is only 20 mm high and 80 mm in diameter. It is made up of two parts - the base which is installed onto a wall or soffit and the lid which is fitted to the base with a bayonet lock.

An anti-tamper screw in the lid locks the unit together.

Two pairs of keyhole fixings are provided - one for 50 mm and the other for 60 mm fixing centers.

## 1.1 Technical data

Specifications are typical at 24V, 25°C and 50% RH unless otherwise stated.

Voltage A and C	5 - 36 V
Max current B and C	25 mA up to 40°C
Operating temperature	-10 °C to +60 °C

### Detector range connections:

ALC2	A ja C
SLC	A ja C
ELC	A ja C

