


ALTEZZO A 120 600MM 850LM 840 IP65 RAL7016 8W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	413285
Rated power of the luminaire [W]*:	8
Ingress protection:	IP65
Impact resistance:	IK08
Luminous flux [lm]*:	850
Colour temperature [K]:	4000
Material of the body:	aluminium
Colour of the body:	RAL7016
Diffuser type:	transparent
Beam angle [°]:	110

CHARACTERISTICS

A family of outdoor lamps with a modern design. The decorative, openwork housing gives the luminaire a lightweight appearance while providing an interesting distribution of accent light. The compact (120mm x 120mm), square cross-section profile of the Altezzo lamps is IK08 impact resistant. It is made of aluminium in graphite (RAL 7016). The light module consists of long-life LEDs with a durable polycarbonate aperture. The lamp will provide energy-efficient lighting and safety for users of outdoor areas.

APPLICATION

They are designed for outdoor use. The high tightness of the lamps allows them to be used in harsh weather conditions. They can operate in very low and high temperatures. They will work well in parks and gardens to illuminate small architecture.

DETAILS

If the dedicated foundation does not provide the safe conditions specified in the design, a suitable one should be selected from outside the lighting manufacturer's offer, with an anchor spacing of 180x180 - 220x220mm. As standard, in the case of Altezzo L100, universal 13kg foundations are used for garden lamps or FBO 35/7.5 M6 foundations for taller posts and/or more difficult ground and water conditions. For Altezzo L150, B-50 universal foundations or B-51 foundations are used for taller posts and/or more difficult soil and water conditions.

ALTEZZO A 120 600MM 850LM 840 IP65 RAL7016 8W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	413285	Colour of the body:	RAL7016
Rated power of the luminaire [W]:	8	Mounting dimensions [mm]:	75/75 - 90/90
EAN:	5905963413285	Impact resistance:	IK08
Colour temperature [K]:	4000	Ingress protection:	IP65
Light source:	LED	Mounting version:	on a foundation
Luminous flux [lm]:	850	Working temperature [°C]:	from -25 to +50
Diffuser type:	transparent	Net weight [kg]:	2.800
Supply voltage [V]:	220 - 240	Category type:	Park and city lighting
Frequency [Hz]:	50 - 60	AC voltage range [V]:	90 - 264
Luminous efficacy [lm/W]:	96	LED lifespan L70B50 [h]:	174000
Dimensions (H/W/T/S) [mm]:	120/120/600	LED lifespan L80B20 [h]:	110000
Energy efficiency class:	E	LED lifespan L90B10 [h]:	53000
Electrical protection class:	I	Light distribution type:	general
Colour rendering index:	>80	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
SDCM:	≤ 3	CE certificate:	180/2023
Beam angle [°]:	110	Manual:	Download PDF
Surge protection [kV]:	2	Plik LDT:	Download
Material of the body:	aluminium		