

## REFLEX

WALL-MOUNTED INDIRECT LIGHT | 72CM

STH9741PTO/30



20W

Power

1450lm

Luminous flux

110° / 110°


Beam angle




### TECHNICAL SPECIFICATIONS TABLE

|                                    |             |
|------------------------------------|-------------|
| Beam angle                         | 110° / 110° |
| Luminous efficacy                  | 73lm/W      |
| Power factor                       | 0,92        |
| Luminous flux                      | 1450lm      |
| Frequency                          | 50/60Hz     |
| Ingress protection rating (IP)     | IP65        |
| CRI (Color rendering index)        | 80          |
| Power                              | 20W         |
| Correlated color temperature (CCT) | 3000K       |
| Voltage (V)                        | 100-240V    |
| Voltage (Vac)                      | 100-240Vac  |
| Lifespan                           | 25000h      |

### Technical Drawing



### Graphics



### OTHER INFORMATION

|                     |                  |
|---------------------|------------------|
| Finishing           | Black            |
| Color temperature   | Warm white       |
| Dimmable            | No               |
| Warranty            | 2 years          |
| Patent information  | Patented product |
| Prevailing material | Aluminum         |

### DOWNLOADS

↓ IES FILE - STH9741PTO/30

↓ MANUAL Reflex

↓ SKETCHUP - STELLA - STH9741BR-27-30 - STH9741PTO-27-30 - REFLEX - ARANDELA DE LUZ INDIRECTA 72cm\_PACK.zip

↓ REVIT - STH9741BR\_27\_PTO\_27\_STH9741BR\_30\_PTO\_30.rfa

