

WALL MINI

WALL-MOUNTED EFFECT LIGHT | 2 WIDE BEAMS

STH9730BR/30



5W

Power

200lm
(100lm/100lm)lm

Luminous flux

70° / 70°°


Beam angle



TECHNICAL SPECIFICATIONS TABLE

Beam angle	70° / 70°°
Power factor	0,92
Luminous flux	200lm (100lm/100lm)
Frequency	50/60Hz
Ingress protection rating (IP)	IP65
CRI (Color rendering index)	80
Power	5W
Correlated color temperature (CCT)	3000K
Operation temperature	-10°C ~ 40°C°C
Voltage (V)	100-240V
Voltage (Vac)	100-240Vac
Lifespan	25000h

Technical Drawing




Graphics

STH9730BR

1m	134lx	0,9m
2m	33lx	1,8m
3m	15lx	2,7m
4m	8lx	3,6m
5m	5lx	4,5m

h, Emax, Ø



OTHER INFORMATION

Finishing	White
Color temperature	Warm white
Dimmable	No
Warranty	2 years
Patent information	Patented product
Prevailing material	Polycarbonate

DOWNLOADS

MANUAL Wall Mini

SKETCHUP - STELLA - STH9730BR-30 - STH9730PTO-30 - WALL MINI - FACHO ABERTO_PACK.zip

REVIT - STH9730BR_30_STH9730PTO_30.rfa

