

## AR70 PRO DIM

DIMMABLE

STL23426/40



4,9W

Power

320lm

Luminous flux

24°


Beam angle




## TECHNICAL SPECIFICATIONS TABLE

|                                    |            |
|------------------------------------|------------|
| Beam angle                         | 24°        |
| Dimming                            | 20-100%    |
| Luminous efficacy                  | 65lm/W     |
| Incandescent equivalence           | 30W        |
| Power factor                       | 0,8        |
| Luminous flux                      | 320lm      |
| Frequency                          | 50/60Hz    |
| CRI (Color rendering index)        | 95(R9 >80) |
| Luminous intensity                 | 1600cd     |
| Correlated color temperature (CCT) | 4000K      |
| Voltage (V)                        | 100-240V   |
| Voltage (Vac)                      | 100-240Vac |
| Lifespan                           | 25000h     |
| Power                              | 4,9W       |
| Register Number                    |            |
| Certifier Number                   |            |
| Certifier                          |            |

## Technical Drawing



## Graphics



## OTHER INFORMATION

|                    |                               |
|--------------------|-------------------------------|
| Base               | GU10                          |
| Color temperature  | Neutral white                 |
| Dimmable           | Yes                           |
| Warranty           | 2 years                       |
| Patent information | Patented product              |
| Power factor       | 0,8                           |
| Current            | 0,040A (127V) / 0,027A (220V) |

## DOWNLOADS

[↓ IES FILE - STL23426/40](#)
[↓ SKETCHUP - STELLA - STL23426-27-30-40 - AR70 PRO DIM 24°\\_PACK.zip](#)
[↓ REVIT - STL23426\\_27\\_30\\_40.rfa](#)
