
## MEGA SQUARE 612366.004.1 | Bollards





Bollards 4051859969204 L 156, B 156, H 1800

free-standing silver, matt (approx. RAL 9006)



Attractive square bollard with innovative housing design and high-quality LED optics. Luminaire tube made of corrosion-resistant aluminium profile, powder coated. Recessed stainless steel fixing plate. Non-corrosive gear compartment made of mould-cast dual compound thermoplastic with integral TP gasket. With membrane valve as a standard to avoid condensed water. Seawater resistant coating. Opal glass: mouth-blown, satin finish. The robust stainless steel mounting base ensures long-term stability. Elongated holes in the base for subsequent and simple alignment of the luminaire. Connection box on base, max. 2 x 3 x 2.5 mm² for through wiring.

**Product specifications** 

Product specifications		
Length L	156 mm	
Width B	156 mm	
Height H	1800 mm	
Weight	14.25 kg	
Light source	LED	
Colour temperature	4000 K	
Rated luminous flux	1700 lm	
System power	18 W	
System efficiency	94 lm/W	
Glare evaluation UGR (4H 8H)	18,5	
	down 180°/180°	
Beam angle	up 180°/180°	
Rated life	50000 h (L80/B50)	
Colour rendering index (CRI)	80	
Colour tolerance	3	
Photobiological safety according to EN 62471	Risk group 1	
Driver	Converter	
Control	on/off	
Voltage	220 - 240 V / 50 Hz, 60 Hz	
Luminaires on B10A fuse	31	
Luminaires on B16A fuse	50	
Luminaires on C10A fuse	52	
Luminaires on C16A fuse	85	
Inrush current / Inrush current duration	5 A / 50 μs	
CIE Flux Code / CEN Flux Code	15 40 69 46 100	
Type of protection	IP 65	
Protection class	I	
Filament test	650 °C	
Impact resistance	IK05	
Ambient temperature	-20 °C + 35 °C	
Conformity mark	CE, EAC	

## MEGA SQUARE 612366.004.1 | Bollards



## **Accessories**



982157.000 Accessory for ground installation

## **Spareparts**



982176.002 Replacement glass