

PRODUCT DATASHEET

Decor Plaster Routes Pendant 150 1XE27

White

Decor Plaster | Decorative luminaires made of plaster with exchangeable light source



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements

Product benefits

- High-quality look and feel
- High flexibility in the choice of the light source
- Sustainable solution thanks to exchangeable light sources
- Easy mounting
- Real wood used by some types

Product features

- Housing material: metal and plaster
- Textile cable



TECHNICAL DATA

Electrical data

| | |
|------------------|---------------|
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Protection class | I |
| Operating mode | Mains voltage |

Dimensions & Weight

| | |
|----------------|------------|
| Diameter | 150.00 mm |
| Height | 1200.00 mm |
| Product weight | 1500.00 g |



DECOR PLASTER ROUTES PEND
150 1XE27

Materials & Colors

| | |
|--|---------|
| Product color | White |
| Housing color | White |
| Body material | Plaster |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |

Application & Mounting

| | |
|--|-----------------------------|
| Ambient temperature range | -20...+40 °C |
| Temperature range at storage | -20...+80 °C |
| Type of connection | Terminal, 3-Pole (L, N, PE) |
| Type of protection | IP20 |
| Protection class IK (shock resistance) | IK03 |
| Dimmable | No |
| Mounting type | Suspended |

| | |
|-------------------------|--------|
| Application environment | Indoor |
| With light source | No |
| Holder designation | E27 |

Certificates & Standards

| | |
|--|-----------|
| Standards | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No |




Additional product data

| | |
|-----------------------|-------------------------------|
| Product remark | Maximum bulb wattage: 6 W LED |
| Number of illuminants | 1 |

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

| | Documents and certificates | Document name |
|--|--|---------------------------|
|  | User instruction / safety instructions | DECOR PLASTER ROUTES PEND |
|  | Declarations of conformity | DECOR LUM |
|  | Declarations of conformity UKCA | DECOR LUM |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075841284 | Folding box 1 | 202 mm x 202 mm x 303 mm | 1760.00 g | 12.36 dm ³ |
| 4058075841291 | Shipping box 2 | 316 mm x 218 mm x 429 mm | 4055.00 g | 29.55 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.