

PRODUCT-DETAILS

TY125-40-39-100

TYFAST 3,6X141MM NATURAL HEAT STAB.



General Information

Extended Product Type	TY125-40-39-100
Product ID	7TCG054360R0131
EAN	5414363060598
Catalog Description	TYFAST 3,6X141MM NATURAL HEAT STAB.
Long Description	Cable Tie, Heat Stabilized Natural Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (221 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 141.48mm (5.57 Inches), Width of 3.556mm (0.140 Inches), Thickness of 1.17mm (0.046 Inches), Tensile Strength Rating of 180 Newtons (40 Pounds), UL Tensile Strength Rating of 133 Newtons (30 Pounds), 100 Pack

Ordering

EAN	5414363060598
UPC	786210840529
Country of Origin	Hungary (HU)
Selling Unit of Measure	each

Dimensions

Product Net Depth / Length	5.57 in 141.48 mm
----------------------------	----------------------

Container Information

Package Level 1 Units	100 piece
Package Level 1 Width	5 in 127 mm
Package Level 1 Height	1 in 25 mm
Package Level 1 Depth / Length	9 in 229 mm
Package Level 2 Units	10000 piece
Package Level 2 Width	10.2 in 259 mm
Package Level 2 Height	13.8 in 351 mm
Package Level 2 Depth / Length	19.7 in 500 mm

Technical UL/CSA

Flammability According to UL94	V-2
--------------------------------	-----

Additional Information

Brand / Label	Catamount
Bundle Diameter	1.25 in 31.75 mm
Color	Natural
Effective Date	20020508
Lock Type	Plastic Pawl
Material	Nylon/Polyamide 6.6
Product Name	OTHER ARTICLES OF PLASTICS
Product Type	Heat Stabilized
Tensile Strength	40 lb 180 N
Thickness	0.046 in 1.17 mm

Certificates and Declarations

Data Sheet, Technical Information	TY125-40-39-100
Declaration of Conformity - CE	9AKK107492A9843

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
ETIM 8	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

