

**PANEL BACKLIGHT MINTAL BLM 40W 4000K  
4000LM IP40 120x30 WHITE UGR19**

CODE: C72-BLM-123-400-4K-WH-U19

EAN: 5900280946997

| Mechanical data           |                                          |
|---------------------------|------------------------------------------|
| Material                  | Aluminum alloy, synthetic material       |
| Mounting method           | Natynkowy/podtynkowy - sufit podwieszany |
| Color                     | Housing: RAL9003                         |
| Electrical data           |                                          |
| Nominal voltage           | Un: ~230V/50Hz                           |
| Power consumption         | Pon: 40W                                 |
| Light data                |                                          |
| Beam angle                | 90°                                      |
| Color rendering index     | CRI>80                                   |
| Color temperature         | 4000K                                    |
| Luminous flux             | 4000lm                                   |
| Installation Data         |                                          |
| Height                    | 28mm                                     |
| Length                    | 1195mm                                   |
| Width                     | 295mm                                    |
| Certificates and markings |                                          |
| Protection class          | Class II                                 |
| Protection degree         | IK03                                     |
| PZH                       | TAK                                      |
| TUV                       | TAK                                      |
| Warranty                  | 5 lat                                    |
| Degree of protection      | IP40                                     |
| Packaging                 |                                          |
| Packaging                 | 6                                        |
| Carton                    | 10                                       |
| Palette                   | 90                                       |
| Other                     |                                          |

|                       |                |
|-----------------------|----------------|
| Durability            | L70B50: 50000h |
| External led driver   | TAK            |
| Operating temperature | -10°C / +45°C  |
| Power factor          | DF>0,9         |
| Product type          | Wyposażony     |
| Brand                 | Bemko          |

