



## IDC interface 16 poles male with LED

|                                                |                                 |
|------------------------------------------------|---------------------------------|
| <b>Series</b>                                  | IF                              |
| <b>Code</b>                                    | XIF16PML                        |
| <b>Type</b>                                    | IF16PML                         |
| <b>HS code</b>                                 | 85369010                        |
| <b>GENERAL TECHNICAL DATA</b>                  |                                 |
| <b>Number of poles</b>                         | 16                              |
| <b>Version</b>                                 | IDC male                        |
| <b>Input rated voltage</b>                     | 0...50 Vac/dc                   |
| <b>Input rated current</b>                     | 750 mA max                      |
| <b>Operating temperature range</b>             | -20...+60°C                     |
| <b>Overvoltage category / pollution degree</b> | II / 2                          |
| <b>Protection degree</b>                       | IP 00                           |
| <b>Connection terminal</b>                     | 2.5 mm <sup>2</sup> screw       |
| <b>Status indication</b>                       | LED (1)                         |
| <b>Dimensions (LxHxD)</b>                      | 58x66x93 mm                     |
| <b>Housing material</b>                        | UL94V-0 plastic material        |
| <b>Mounting information</b>                    | vertical on rails, side by side |
| <b>ACCESSORIES</b>                             |                                 |
| <b>Mounting rail (IEC60715/TH35-7.5)</b>       | PR003, PR903, PR005, PR925      |
| <b>Mounting rail (IEC60715/TH35-15)</b>        | PR007, PR907, PR006, PR926      |
| <b>APPROVALS AND MARKINGS</b>                  | CE                              |



\* Universal module

1 The terminal number corresponds to the connector number 2 (1) Status LEDs are configured for a nominal voltage of 24 Vdc and negative common

## DESCRIZIONE DEL PRODOTTO

IF16PML IDC interface 16 poles  
male with LED