

S.GROUND

LED SPIKE WITH ANTI-GLARE GRID

STL23764/30



6,5W

Power

360lm

Luminous flux

14°

Beam angle




TECHNICAL SPECIFICATIONS TABLE

Beam angle	14°
Luminous efficacy	55lm/W
Power factor	0,92
Luminous flux	360lm
Frequency	50/60Hz
Ingress protection rating (IP)	IP67
CRI (Color rendering index)	80
Luminous intensity	3200cd
Power	6,5W
Correlated color temperature (CCT)	3000K
Voltage (V)	100-240V
Voltage (Vac)	100-240Vac
Lifespan	25000h

Technical Drawing

STL23764




Graphics

STL23764

1m	2926lx	0,3m
2m	731lx	0,6m
3m	325lx	0,9m
4m	183lx	1,2m
5m	117lx	1,6m

h, Emax, Ø

STL23764



— C0/180 — C90/270

OTHER INFORMATION

Finishing	Black
Color temperature	Warm white
Dimmable	No
Warranty	2 years
Patent information	Patented product
Prevailing material	Aluminum

DOWNLOADS

[↓ IES FILE - STL23764/30](#)
[↓ MANUAL S.Ground](#)
[↓ SKETCHUP - STELLA - STL23764-30 - ESPETO GROUND 6W COM GRADE_PACK.zip](#)
[↓ REVIT - STL23764_30.rfa](#)
