


MADERA 3 LED 620X350MM 2550LM 840 IP44 OPAL GRAY (21W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44
Nominal power [W]:	21
Luminous flux [lm]*:	2550
Colour rendering index:	>80
Energy efficiency class:	E
Material of the body:	powder coated steel
Diffuser material:	PS
Diffuser type:	OPAL
Mounting version:	surface

CHARACTERISTICS

Surface mounted, square LED fitting with high luminous flux, made of steel sheet, powder-coated grey; equipped with energy-saving light source LED-GO!. OPAL or PRM PMMA diffuser ensures even light distribution and no glare effect. Decorative fitting available in two diffuser sizes; optional equipment: radio motion sensor (RCR).

APPLICATION

Surface-mounted luminaire intended for indoor use in offices or common rooms. Suitable as a general light source in representative rooms. Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms. Product designed for surface mounting either on ceilings or on walls.

MADERA 3 LED 620X350MM 2550LM 840 IP44 OPAL GRAY (21W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	21	Diffuser material:	PS
Index:	497360	Material of the body:	powder coated steel
Colour temperature [K]:	4000	Mounting dimensions [mm]:	265/495
EAN:	5905963497360	Ingress protection:	IP44
Luminous flux [lm]:	2550	Mounting version:	surface
Light source:	LED module	Net weight [kg]:	4.100
Diffuser type:	OPAL	Warranty [years]:	5
Rated power of the luminaire [W]:	23	CE certificate:	254/2023
Colour of the body:	grey	Category type:	louvres
Supply voltage [V]:	220-240	Luminaire rated power P_{min} [W]:	22.60
Dimensions (H/W/T/S) [mm]:	620/350/68	LED lifespan L70B50 [h]:	95000
Frequency [Hz]:	50 - 60	LED lifespan L80B20 [h]:	60000
Energy efficiency class:	E	LED lifespan L90B10 [h]:	29000
Luminous efficacy [lm/W]:	113	Light distribution type:	lamertian
Electrical protection class:	I	Manual:	Download PDF
Colour rendering index:	>80	Plik LDT:	Download