


# TRIONA square

312655.004.730 | Pendant luminaires



Pendant luminaires  
4051859919698  
L 567, B 567, H 52

pendant  
silver, matt (approx. RAL 9006)



Decorative square LED pendant-mounted surface luminaire. Flat, seamless frame: aluminium extrusion profile, powder coated. Cover made of sheet steel, powder-coated. Canopy made of aluminium, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. LED back-light technology for homogeneous illumination of the entire light-emitting surface. 4-point steel cable suspension, steplessly adjustable. Easy installation with transparent, adjustable pendant cable and canopy with magnetic fixing. Driver integrated. Dimmable DALI. Suitable for through-wiring. With Casambi smart+free Bluetooth® control for wireless network and operation using Android / iOS devices, free app available for download.

## Product specifications

Length L	567 mm
Width B	567 mm
Height H	52 mm
Suspension length LP	500-1200 mm
Weight	9.5 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux	6150 lm
System power	51 W
System efficiency	121 lm/W
Glare evaluation UGR (4H 8H)	23,1
Beam angle	107°
Rated life	50000 h (L90/B50)
Colour rendering index (CRI)	80
Colour tolerance	4
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	smart+free (Bluetooth)
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	12
Luminaires on B16A fuse	20
Luminaires on C10A fuse	21
Luminaires on C16A fuse	33
Inrush current / Inrush current duration	20 A / 200 µs
CIE Flux Code / CEN Flux Code	48 79 96 100 100
Type of protection	IP 20
Protection class	I
Filament test	650 °C
Impact resistance	IK03
Ambient temperature	-20 °C ... + 35 °C
Conformity mark	CE