


# LEVIDO round

901832.002.76 | Recessed downlights



Recessed downlights  
4051859944218  
D 91, H 2

Recessed ceiling mounting  
traffic white, matt (RAL 9016)



Decorative round recessed downlight with daintily small dimensions. Die-cast aluminium cover, powder-coated. Heat sink die-cast aluminium. Reflector: aluminium, highly polished anodised finish. With safety glass. Wide beam light distribution. Light beam 52°. MultiLumen: 2 steps adjustable luminous flux. Factory setting is the highest luminous flux. Suitable for Recessed ceiling mounting. Ceiling installation with spring system. Including separate LED converter with connecting cable 250 mm. Suitable for through-wiring. Opal diffuser (PMMA) for uniform, homogenous light distribution available as an accessory.

### Product specifications

Diameter D	91 mm
Height H	2 mm
Cut-out diameter DA	78 mm
Luminaire: recess height HEL	95 mm
Ceiling thickness S	1-20 mm
Installation space length LE	200 mm
Installation space width BE	200 mm
Installation space height HE	95 mm
Weight	398 g
Light source	LED
Colour temperature	3000 K
Rated luminous flux	710 lm   1100 lm
System power	7.5 W   12 W
System efficiency	92 lm/W   95 lm/W
Glare evaluation UGR (4H 8H)	18,8   20,3
Beam angle	52°
Rated life	50000 h (L90/B50)
Colour rendering index (CRI)	80
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	66
Luminaires on B16A fuse	106
Luminaires on C10A fuse	66
Luminaires on C16A fuse	106
Inrush current / Inrush current duration	4.24 A / 42 µs
CIE Flux Code / CEN Flux Code	90 96 99 100 100
Type of protection	IP 44 on room side IP 20
Protection class	II
Filament test	850 °C
Impact resistance	IK06
Ambient temperature	5 °C ... + 35 °C
Safety marks	Do not cover the recessed luminaire!
Conformity mark	CE, EAC

# LEVIDO round

901832.002.76 | Recessed downlights



## Accessories



982184.002  
Cover: plastic, opal.