

PRODUCT DATASHEET

Orbis Disc 30X30CM 22W Click CCT IP44 White

Orbis Disc | Luminaires with two adjustable color temperatures via wall switch and protection class IP44



Areas of application

- Indoor
- Living areas (living rooms, dining rooms, bedrooms etc.)
- Bathrooms (IP44)

Product benefits

- Easy to install and use
- Long lifetime thanks to LED technology

Product features

- Type of protection: IP44
- Lifetime up to 30,000 h
- Color temperature: 3,000 K (Warm White) or 4,000 K (Neutral White)
- Click-CCT version: color temperature adjustable in two steps by repeated switching
- Available in square and rectangular form
- Housing material: aluminum
- Polycarbonate (PC) diffuser



TECHNICAL DATA

Electrical data

| | |
|---|---------------------|
| Nominal wattage | 22.00 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Nominal current | 116.000 mA |
| Inrush current | 0.116 A |
| Inrush current time T_{h50} | 566 μ s |
| Max. number of luminaires per miniature circuit breaker B16 | 16 |
| Max. number of luminaires per miniature circuit breaker C10 | 17 |
| Max. number of luminaires per miniature circuit breaker C16 | 28 |
| Power factor λ | > 0.7 |
| Total harmonic distortion | < 80 % |
| Protection class | II |
| Operating mode | External LED driver |


Photometrical data

| | |
|--|-------------------------|
| Luminous flux | 1800 lm |
| Total luminous flux of contained light sources | 2880 lm |
| Luminous efficacy | 81 lm/W |
| Color temperature | 3000 ... 4000 K |
| Reference control setting of contained light source (Kelvin) | 3000 K |
| Light color (designation) | Warm White / Cool White |
| Color rendering index Ra | \geq 80 |
| Standard deviation of color matching | 6 sdc _m |
| Flickering metric (Pst LM) | < 1 |
| Stroboscope effect metric (SVM) | < 0.4 |
| Photobiological safety group acc. to EN62778 | RG0 |
| Photobiological safety group acc. to EN62471 | RG0 |
| Beam angle | 120 ° |

Dimensions & Weight

| | |
|--------|-----------|
| Length | 300.00 mm |
| Width | 300.00 mm |
| Height | 30.00 mm |

| | |
|----------------|----------|
| Product weight | 910.00 g |
|----------------|----------|



ORBIS DISC 30X30 22W
CLICKCCTIP44

Materials & Colors

| | |
|--|--|
| Product color | White |
| Housing color | White |
| Body material | Polycarbonate (PC) Acrylonitrile butadiene styrene (ABS) |
| Cover material | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |

Application & Mounting

| | |
|------------------------------|-------------------------|
| Ambient temperature range | -20...+40 °C |
| Temperature range at storage | -20...+80 °C |
| Type of connection | Terminal, 2-Pole (L, N) |
| Type of protection | IP44 |
| Dimmable | No |
| Mounting type | Surface |
| Mounting location | Wall |
| Application environment | Indoor |
| With light source | Yes |

Lifespan

| | |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 30000 h ¹⁾ |
| Number of switching cycles | 10000 |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

| | |
|--|-----------------|
| Standards | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No |
| Replaceable light source (EPREL) | Not replaceable |




EQUIPMENT / ACCESSORIES

- Mounting screws and dowels included

Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

| Documents and certificates | Document name |
|--|------------------------------------|
|  User instruction / safety instructions | ORBIS DISC 30SQ 22W CLC |
|  Declarations of conformity | ORBIS MIRROR ORBIS TUBE ORBIS DISC |
|  Declarations of conformity UKCA | ORBIS MIRROR ORBIS TUBE ORBIS DISC |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854279676 | Folding box 1 | 37 mm x 317 mm x 318 mm | 1033.00 g | 3.73 dm ³ |
| 4099854279683 | Shipping box 4 | 335 mm x 335 mm x 175 mm | 4685.00 g | 19.64 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.