


1 electromechanical relay 24Vdc  
SPST(NA) 5A, screw, not pluggable

<b>Series</b>	
Code	XRFA024D
Type	RFA024D (1)
HS code	85364190
<b>INPUT TECHNICAL DATA</b>	
Input rated voltage	24 Vdc ±10%
Pull in / drop out voltage type	18.4 V / 2.4 V
Current consumption	15 mA ±10%
Turn ON / OFF time	15 ms / 5 ms
Protection circuit	Free-wheel diode, Reverse polarity
Connection terminal	2.5 mm <sup>2</sup> screw
Input channels	1 not pluggable
<b>OUTPUT TECHNICAL DATA</b>	
Contact type	SPST(NO), 1 Form A (NO), AgSnO <sub>2</sub>
Nominal current	5 A (250 Vac)
Continuous current	10 A
Min applicable load	100 mA / 5 Vdc
Connection type	
<b>GENERAL TECHNICAL DATA</b>	
Operating temperature range	-20...+70°C
Input / output isolation	2.5 kVac / 60 s
Protection degree	IP 00
Overvoltage category / pollution degree	II / 2
Status indication	LED "Input"
Housing material	UL94V-0 plastic material
Dimensions (LxHxD)	12x77x52 mm
Approximate weight	30 g
Mounting information	on a rail, side by side
<b>ACCESSORIES</b>	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail (IEC60715/TH35-15)	PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB
Spare part relay	8904075
APPROVALS AND MARKINGS	CE,



\* Not-pluggable relay  
1 Manufacturer and model of the relay is not binding, technical data are to be considered typical2 (1) Version produced upon request; contact our sales office for availability.

## DESCRIZIONE DEL PRODOTTO

RFA024D  
1 electromechanical relay 24Vdc SPST(NA) 5A, screw, not pluggable