

TRIONA round

312421.0031.730 | Pendant luminaires



Pendant luminaires
4051859434795
D 461, H 52

pendant
anthracite metallic (DB703)



Decorative round LED pendant-mounted surface luminaire. Flat, seamless frame: aluminium extrusion profile, powder coated. Cover made of sheet steel, powder-coated. Canopy made of aluminium, powder-coated. Light emission through a diffuser: plastic, opal. Lightguide and diffuser made of non-yellowing plastic (PMMA). Lateral light emission (RZB SIDELITE® technology) for above-average homogeneous light distribution. 3-point steel cable suspension, steplessly adjustable. Easy installation with transparent, adjustable pendant cable and canopy with magnetic fixing. Driver integrated.

Product specifications

Diameter D	461 mm
Height H	52 mm
Suspension length LP	500-1200 mm
Weight	4.96 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux	4650 lm
System power	48 W
System efficiency	97 lm/W
Glare evaluation UGR (4H 8H)	24,4
Beam angle	107°
Rated life	50000 h (L80/B50)
Colour rendering index (CRI)	80
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	smart+free (Bluetooth)
Voltage	220 - 240 V / 50 Hz
Luminaires on B10A fuse	8
Luminaires on B16A fuse	13
Luminaires on C10A fuse	14
Luminaires on C16A fuse	22
Inrush current / Inrush current duration	53 A / 200 µs
CIE Flux Code / CEN Flux Code	49 80 96 100 100
Type of protection	IP 20
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK03
Ambient temperature	25 °C
Conformity mark	CE, EAC