


CORIA 2 14800LM 1200MM DALI I CL. IP40 SUSPENDED BLACK MAT 840 145W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	276118
Ingress protection:	IP40
Rated power [W] - range:	145
Luminous flux of the luminaire [lm] - range:	14800
Colour temperature [K]:	4000
Colour rendering index:	>80
Electrical protection class:	I
Material of the body:	aluminium
Colour of the body:	black

CHARACTERISTICS

The Coria 2 LED circular luminaire with integrated energy-efficient LED module is characterised by its high luminous efficacy and uniform light distribution. Its base is made of white or black powder-coated aluminium and its diffuser is made of microprism (300mm diameter version only) or opal plastic. It is ideal for new applications and for replacing traditional fluorescent lamps with energy-efficient LED solutions. Characteristics: colour temperature 3000K, 4000K; CRI>80; LED module life 119,000 hours (L80B20) ta = 25°C; pendant or surface-mounted version.

APPLICATION

The luminaire is designed for indoor use. It is characterised by even light distribution and good surface illumination, which is why it is particularly dedicated as a source of general light in representative rooms and passageways. Thanks to its excellent luminous parameters, the luminaire is ideal for large conference rooms. The luminaire's construction has been adapted for surface-mounted or flush-mounted installation in plasterboard ceilings. Revit files for architectural luminaires are available on request.

CORIA 2 14800LM 1200MM DALI I CL. IP40 SUSPENDED BLACK MAT 840 145W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	276118	Ingress protection:	IP40
EAN:	5905963276118	Mounting version:	suspended
Light source:	LED	Working temperature [°C]:	from -10 to +35
Rated power [W] - range:	145	Dimensions of single box [mm]:	1290
Colour temperature [K]:	4000	Number on the palette [pcs]:	5
Luminous flux of the luminaire [lm] - range:	14800	Net weight [kg]:	17.400
Diffuser type:	OPAL	Category type:	bulkheads
Luminous efficacy [lm/W]:	103	LED lifespan L70B50 [h]:	189000
Energy efficiency class:	E	LED lifespan L80B20 [h]:	119000
Electrical protection class:	I	LED lifespan L90B10 [h]:	57000
Colour rendering index:	>80	Light distribution type:	lambertian
Diffuser material:	PC	SDCM:	≤ 3
Colour of the body:	black	Warranty [years]:	5
Material of the body:	aluminium	CE certificate:	04/2024
DIMM DALI:	yes	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	1200/86	Plik LDT:	Download
Mounting dimensions [mm]:	109/109		

LIGHT CURVES

