


DEECOS P micro

911490.003.2.76 | Pendant luminaires



Pendant luminaires
4051859739647
D 60, H 190

pendant
deep black, matt (RAL 9005)




Cylindrical pendant luminaire. Housing: die-cast aluminium, powder-coated. Canopy made of powder-coated sheet steel with magnetic attachment. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. Black plastic ring and recessed LED to prevent glare from the side. Best colour rendering index Ra>90. Transparent suspension cable 3 m, can be shortened. High quality converter without flickering and stroboscopic effect.

Product specifications

Diameter D	60 mm
Height H	190 mm
Suspension length LP	3000 mm
Weight	0.89 kg
Light source	LED
Colour temperature	4000 K
Rated luminous flux	1350 lm
System power	16 W
System efficiency	84 lm/W
Glare evaluation UGR (4H 8H)	22,6
Beam angle	52°
Rated life	50000 h (L80/B10)
Colour rendering index (CRI)	92
Colour tolerance	2
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	21
Luminaires on B16A fuse	34
Luminaires on C10A fuse	35
Luminaires on C16A fuse	57
Inrush current / Inrush current duration	18 A / 250 µs
CIE Flux Code / CEN Flux Code	92 99 100 100 100
Type of protection	IP 20
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK06
Ambient temperature	25 °C
Conformity mark	CE

Accessories

	982801.003 Anti-glare honeycomb louvre		982802.000 Diffuser, transparent
	982802.010 Diffuser, satinated		982803.003 Reflector spot
	982803.013 Reflector flood		982804.013 Medium lens
	982804.023 Wide flood lens		982805.003 Oval corridor lens
	982806.002 White plastic ring for reflector.		982807.002 White plastic ring for lens.