



Ledinaire floodlights gen3

BVP164 LED11/830 PSU 10W SWB CE

- - - 830 warm white - - - Symmetrical

This Ledinaire floodlights range contains a selection of popular off-the-shelf LED luminaires that comes with the Philips high quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need.

Product data

General Information		Luminaire light beam spread	
Lamp family code	-	Luminaire light beam spread	110° x 110°
Light source replaceable	No	Optic type outdoor	Symmetrical wide beam
Number of gear units	1 unit	Operating and Electrical	
Driver included	Yes	Input Voltage	220 to 240 V
Light source engine type	LED	Line Frequency	50 or 60 Hz
Service tag	No	Input Frequency	50 or 60 Hz
Lighting Technology	LED	Initial CLO power consumption	- W
Light Technical		Average CLO power consumption	10 W
Upward light output ratio	0	Power Consumption	10 W
Luminous Flux	1,100 lumen	End CLO power consumption	- W
Standard tilt angle posttop	-	Inrush current	0.78 A
Standard tilt angle side entry	-	Inrush time	0.00648 ms
Correlated Color Temperature (Nom)	3000 K	Power Factor (Fraction)	0.95
Luminous Efficacy (rated) (Nom)	110 lm/W	Connection	Flying leads/wires
Color rendering index (CRI)	>80	Cable	Cable 1.0 m without plug
Light source color	830 warm white	Number of products on MCB of 16 A type B	210
Optical cover/lens type	Glass		

Ledinaire floodlights gen3

Temperature	
Ambient temperature range	-25 to +40 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (ON/OFF)
Control interface	-
Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum die cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover/lens material	Tempered glass
Fixation material	Steel
Housing Color	Gray
Mounting device	Mounting bracket adjustable
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	79 mm
Overall width	111 mm
Overall height	25.5 mm
Effective projected area	0.005 m ²
Dimensions (Height x Width x Depth)	26 x 111 x 79 mm
Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Surge Protection (Common/Differential)	2/2 kV
Sustainability rating	-
Protection class IEC	Safety class I
Flammability mark	-
CE mark	Yes
ENEC mark	-

Warranty period	3 years
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.440, 0.403) SDCM <5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	80

Application Conditions


Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable

Product Data

Full product code	871951453364699
Order product name	BVP164 LED11/830 PSU 10W SWB CE
Order code	911401841483
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material number (12NC)	911401841483
Full product name	BVP164 LED11/830 PSU 10W SWB CE
EAN/UPC - Case	8719514533882



Dimensional drawing



Ledinaire floodlights gen3

