

PRODUCT DATASHEET

Decor Aura Table 10W 830 Touch DIM USB

Decor Aura | Decorative lights made of polycarbonate with integrated LED and an eye-catching filament design



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements

Product benefits

- Even filament illumination
- Click dim function by wall switch for pendant and ceiling types
- Different types of luminaires with the same design language maintain a consistent style at home
- Minimalistic style fits to every room
- Combined modern table luminaire with a USB-C charging outlet
- 3-step selecting by wall switch to turn on indirect and direct lights separately (click select)
- Easy mounting

Product features

- Housing material: polycarbonate (PC)
- High-power LED



TECHNICAL DATA

Electrical data


Nominal wattage	10.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	68.000 mA
Inrush current	0.07 A
Inrush current time T_{h50}	150 μ s
Max. number of luminaires per miniature circuit breaker B16	95
Max. number of luminaires per miniature circuit breaker C10	80
Max. number of luminaires per miniature circuit breaker C16	128
Power factor λ	≥ 0.5
Total harmonic distortion	< 100 %
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	1000 lm
Total luminous flux of contained light sources	1200 lm
Luminous efficacy	90 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	6 sdc _m
Flickering metric (Pst LM)	< 1
Stroboscope effect metric (SVM)	< 0,4
Photobiological safety group acc. to EN62778	RG0
Beam angle	360 °

Dimensions & Weight

Length	367.00 mm
Width	150.00 mm
Height	349.00 mm
Product weight	680.00 g
Cable length	1.4 m



DECOR AURA TABLE 10W830
TOUCH D USB

Materials & Colors

Product color	Dark gray
Housing color	Dark gray
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Plug type C (EU)
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	Yes
Type of dimming	Push DIM
Mounting type	Standing
Application environment	Indoor
Adjustable	No
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	25000 h ¹⁾
---------------------------	-----------------------

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE
-----------	----

Replaceable light source (EPREL)

Not replaceable

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	DECOR AURA TABLE TOUCH D USB
 Declarations of conformity	DECOR AURA SWIRL TOUCH

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075842120	Folding box 1	176 mm x 393 mm x 383 mm	1074.00 g	26.49 dm ³
4058075842137	Shipping box 2	404 mm x 364 mm x 413 mm	3028.00 g	60.73 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.