




Ceiling luminaires
4051859448280
L 1202, B 302, H 47

Ceiling mounting
white



High-efficiency LED louvre surface-mounted luminaire. Housing: metal, powder-coated. Alea optical system: Reflector structure (ABS, Aluminium-coated, highly polished) with integrated diffuser made of non-yellowing plastic (PMMA) opal for glare-free light at the workstation. Narrow beam, brilliant luminous effect. Suitable for Ceiling mounting. Driver integrated. Perfect for office areas ($UGR \leq 19$) and environments with computer screens in accordance with EN 12464-1.

Product specifications

Length L	1202 mm
Width B	302 mm
Height H	47 mm
Weight	6.32 kg
Light source	LED
Colour temperature	4000 K
Rated luminous flux	3450 lm
System power	26 W
System efficiency	133 lm/W
Glare evaluation UGR (4H 8H)	18,5
Beam angle	78°/75°
Rated life	50000 h (L80/B10)
Colour rendering index (CRI)	80
Colour tolerance	4
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	14
Luminaires on B16A fuse	22
Luminaires on C10A fuse	23
Luminaires on C16A fuse	37
Inrush current / Inrush current duration	40.8 A / 100 μ s
CIE Flux Code / CEN Flux Code	82 100 100 100 100
Type of protection	IP 20
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK03
Ambient temperature	-20 °C ... + 40 °C
Conformity mark	CE, EAC