

TERRANO 600X30MM 1150LM 830 II CL. WHITE 60D (9W)

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Rated power of the luminaire [W]*:	9
Luminous flux [lm]*:	1150
Supply voltage [V]:	220-240
Energy efficiency class:	G
Electrical protection class:	II
Colour temperature [K]:	3000
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	17/568/33

CHARACTERISTICS

The new linear luminaire in the form of a compact louver with LEDs and focusing lenses enables extremely effective glare reduction (UGR between 12 and 19). Terrano luminaires are characterised by excellent performance and many conveniences. Above all, it can be installed quickly on the supporting structure of a modular ceiling. The same luminaire can be relocated just as quickly. Changing the location will leave no trace of the mounting holes. For convenience and aesthetics, the luminaire has an extra-thin power cable, which fits between the structure and the ceiling tile. Terrano, a plastic luminaire in a slim steel housing, is available in two colour temperatures, 3000 K and 4000 K, and in two colours, white and black.

APPLICATION

Terrano can be fitted directly into modular ceiling profiles to provide general lighting, but can also be used to spotlight selected elements of a space. Terrano will become both a striking element of modern arrangements where lighting plays a key role and a complement to subtle, minimalist spaces.

*DUO- version of double lamp on one power supply


TERRANO 600X30MM 1150LM 830 II CL. WHITE 60D (9W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	937231	Diffuser type:	matrix led
EAN:	5905963937231	Diffuser colour:	transparent
Light source:	LED module	Optics:	lens
Rated power of the luminaire [W]:	9	Optics material:	PMMA
Colour of the body:	white	Material of the body:	powder coated steel
Luminous flux [lm]:	1150	Dimensions (H/W/T/S) [mm]:	17/568/33
Colour temperature [K]:	3000	Ingress protection:	IP20
Supply voltage [V]:	220-240	Mounting version:	to T-profile ceilings suspended
Frequency [Hz]:	50-60	Working temperature [°C]:	from -10 to +35
Luminous efficacy [lm/W]:	128	LED lifespan L70B50 [h]:	156000
Energy efficiency class:	G	LED lifespan L80B20 [h]:	98000
Electrical protection class:	II	LED lifespan L90B10 [h]:	47000
Colour rendering index:	>80	Net weight [kg]:	0.390
SDCM:	≤ 3	Manual:	Download PDF
Beam angle [°]:	60	CE certificate:	68/2025
Light distribution type:	symmetric	Category type:	louvres
Surge protection [kV]:	1	Pliik LDT:	Download
Diffuser material:	PMMA		

LIGHT CURVES



TERRANO 600X30MM 1150LM 830 II CL. WHITE 60D (9W)


DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
937408	Terrano white connector
937415	Terrano black connector
420931	Terrano surface frame white gloss RAL9003 573x38x60
420948	Terrano surface frame black mat RAL9005 573x38x60



Terrano white connector (937408)



Terrano black connector (937415)



Terrano surface frame white gloss
RAL9003 573x38x60 (420931)



Terrano surface frame black mat
RAL9005 573x38x60 (420948)

Card creation date: 02 June 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 68/2025