

# Ceasr Opera, walk over

96700861 CESAR OPERA L WO 24L 930 WB HFX ANT

THORN

LED 10W CESA_OP_L_WB_930	IP67	IK09			
--------------------------	------	------	---	---	--


## Ceasr Opera, walk over

Ceasr Opera, walk over a floor recessed, architectural LED luminaire for decorative facade lighting, wide beam distribution. DALI-2 dimmable LED driver. Class I electrical, IP67, Impact strength: IK09. Housing: die-cast aluminium, powder coated anthracite. Working ambient temperature: -20°C to +45°C. Complete with 3000K LED.


Dimensions: Ø210 x 240 mm  
Luminaire input power: 9.8 W  
Luminaire luminous flux: 92 lm  
Luminaire efficacy: 9 lm/W  
Weight: 2.94 kg



TLG\_CESA\_F\_OPERA\_L\_WO\_WB\_ANT.jpg



TLG\_CESA\_M\_OPERA\_L\_WO.wmf



96700861.ltd

Lamp position: STD - standard  
Light Source: LED  
Luminaire luminous flux\*: 92 lm  
Luminaire efficacy\*: 9 lm/W  
Colour Rendering Index min.: 90  
Correlated colour temperature\*: 3000 Kelvin

Chromaticity tolerance (initial MacAdam): 3  
Rated useful life (B10)\*:  
L80 70000 h at 25 °C  
Ballast: 1x LED\_DRV  
Luminaire input power\*: 9.8 W  
Dimming: Dali2Dim  
LOR: 1,00 ULOR: 1,00 DLOR: 0,00

This product contains a light source of energy efficiency class E.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting