

## DEEP

RECESSED PANEL

STH8903BR/50

17W

Power

1500lm

Luminous flux

120°

Beam angle




## TECHNICAL SPECIFICATIONS TABLE

|                                    |            |
|------------------------------------|------------|
| Beam angle                         | 120°       |
| Luminous efficacy                  | 88lm/W     |
| Power factor                       | 0,92       |
| Luminous flux                      | 1500lm     |
| Frequency                          | 50/60Hz    |
| CRI (Color rendering index)        | 80         |
| Power                              | 17W        |
| Correlated color temperature (CCT) | 5000K      |
| Voltage (V)                        | 100-240V   |
| Voltage (Vac)                      | 100-240Vac |
| Lifespan                           | 25000h     |

## Technical Drawing

STH8903




## Graphics

STH8903BR

|    |       |       |
|----|-------|-------|
| 1m | 543lx | 2,6m  |
| 2m | 136lx | 5,1m  |
| 3m | 60lx  | 7,7m  |
| 4m | 34lx  | 10,3m |
| 5m | 22lx  | 12,8m |

h, Emax, Ø

STH8903BR



## OTHER INFORMATION

|                     |                  |
|---------------------|------------------|
| Finishing           | White            |
| Dimmable            | No               |
| Warranty            | 2 years          |
| Patent information  | Patented product |
| Prevailing material | Polycarbonate    |

## DOWNLOADS

[↓ IES FILE - STH8903BR/50](#)[↓ MANUAL DEEP](#)[↓ SKETCHUP - STELLA - STH8903BR-30-40-50 - STH8903PTO-30-40 - PAINEL DE EMBUTIR RECUADO DEEP 18W\\_PACK.zip](#)[↓ REVIT - STH8903BR\\_30\\_40\\_50\\_STH8903PTO\\_30\\_40.rfa](#)