


LIGHTSTREAM maxi

722289.0031.1.76 | Spotlights



Spotlights
4051859957492
L 743, B 291, H 56

Pole mounting, Universal mounting system
anthracite metallic (DB703)



Clever combination of spotlight and pole luminaire in one. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. Tilt angle can be adjusted and locked in 5 degree steps featuring angular scale. With membrane valve as a standard to avoid condensed water. Cover clear single-pane toughened glass, edge printed. Cover screwed to housing. Lens system made of plastic (PMMA). Replaceable LED spot modules according to ZHAGA standards. Symmetrical light distribution. Constant light output (CLO). With NFC programming interface. Pre-assembled connection cable, length 0.5 m. Modular design: Mounting set must be ordered separately.

Product specifications

Length L	743 mm
Width B	291 mm
Height H	56 mm
Weight	7.9 kg
Light source	LED
Colour temperature	4000 K
Rated luminous flux	38500 lm
System power	248 W
System efficiency	155 lm/W
Glare evaluation UGR (4H 8H)	23,3
Beam angle	22°
Rated life	100000 h (L90/B50)
Colour rendering index (CRI)	70
Colour tolerance	5
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	2
Luminaires on B16A fuse	4
Inrush current / Inrush current duration	124 A / 330 µs
CIE Flux Code / CEN Flux Code	84 96 99 100 100
Type of protection	IP 66
Protection class	I
Filament test	960 °C
Impact resistance	IK08
Ambient temperature	-20 °C ... + 40 °C
Conformity mark	CE

Accessories



61199.009
Fuse box



982638.003
Junction box H with strain relief.

LIGHTSTREAM maxi

722289.0031.1.76 | Spotlights



982977.003



982974.003



982588.000
Pole bracket for 2 luminaires, uncoated



982588.0031
Pole bracket for 2 luminaires, powder-coated



982589.000
Pole bracket for 3 luminaires, uncoated



982589.0031
Pole bracket for 3 luminaires, powder-coated



982590.000
Pole bracket for 4 luminaires, uncoated



982590.0031
Pole bracket for 4 luminaires, powder-coated



982591.000
Wall bracket, uncoated



982591.0031
Wall bracket, powder-coated



982562.000
Reducing adapter Ø 60 mm



982983.000
Reducing adapter Ø 42 mm

Modules



982978.0031
Pole attachment for 76 mm spigot.



983117.0031
Mounting bracket