

TIUNNE PLUS 160 2900LM 840 DALI 60D WHITE IP65/IP20 REFLECTOR S 31W

DETAILED CARD



TIUNNE PLUS 160 2900LM 840 DALI 60D WHITE IP65/IP20 REFLECTOR S 31W

DETAILED CARD

TECHNICAL PARAMETERS

Index:	417641
Ingress protection:	IP65
Rated power of the luminaire [W]*:	31
Luminous flux [lm]*:	2900
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	white
Diffuser material:	PC

CHARACTERISTICS

Tiunne Plus is a decorative downlight luminaire for installation in suspended ceilings. It is energy-efficient and durable thanks to the COB LED light source used. It has a classic circular shape that blends in with any type of space. It is available in several versions with different light distribution angles and four reflector colours.

The lamp housing designed in aluminium ensures optimum working conditions for the LEDs, and the aluminium reflector guarantees high luminous efficiency and low glare - features that distinguish the best LED downlight luminaires. The luminaire is suitable for installation in plasterboard and modular ceilings. Colour temperature 3000K, 4000K; CRI>80, CRI>90.

APPLICATION

The luminaire is designed for indoor use as general lighting. It is ideal for walkways, entrance areas, shop windows and fitting rooms in commercial premises.

DETAILS

LED lifespan: L70F50 >60 000h; L80F10 >60 000h; L90F10 57 000h


TIUNNE PLUS 160 2900LM 840 DALI 60D WHITE IP65/IP20 REFLECTOR S 31W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	31	Ring colour:	white
Index:	417641	Material of the body:	aluminium
Colour temperature [K]:	4000	Dimensions (H/W/T/S) [mm]:	ø170/98
EAN:	5905963417641	Colour of the body:	white
Luminous flux [lm]:	2900	Ring material:	aluminium
Light source:	COB	Mounting dimensions [mm]:	160
Luminous efficacy [lm/W]:	94	Ingress protection:	IP65
Energy efficiency class:	E	DIMM DALI:	yes
Colour rendering index:	>80	Mounting version:	recessed
Electrical protection class:	II	Net weight [kg]:	0.550
Beam angle [°]:	60	Category type:	downlights
Optics:	reflector S	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	469/2023
Diffuser type:	transparent	Manual:	Download PDF
Optics material:	aluminium		

LIGHT CURVES



TIUNNE PLUS 160 2900LM 840 DALI 60D WHITE IP65/IP20 REFLECTOR S 31W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
416835	Masking ring 198/257 Tiunne Plus 200 RAL9016
416859	Masking ring 198/257 Square Tiunne Plus 200 RAL9016