


SQ 300 LED PLUS LENS 2100LM 830 IP54 II KL. DALI OPAL (24W) 300MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	664250
Ingress protection:	IP54
Impact resistance:	IK08
Nominal power [W]:	24
Luminous flux [lm]*:	2100
Colour temperature [K]:	3000
Energy efficiency class:	F
Material of the body:	ABS
Diffuser material:	PS
Diffuser type:	OPAL

CHARACTERISTICS

SQ 300 LED is a new line of square ceiling lamps. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, thanks to which it is characterized by low weight and high impact resistance (IK08). The diffuser made of PC polycarbonate provides the lamp with excellent lighting properties. Integrated LED module provides low power consumption and all the advantages of modern lamps with an LED source. The PLUS version of the luminaire line is equipped with brand components from recognized global manufacturers. It is characterized by extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

APPLICATION

The surface-mounted lamp for ceiling or wall mounting is intended for both indoor use - in rooms with high humidity, passageways, staircases, and outdoor use as façade lighting.

SQ 300 LED PLUS LENS 2100LM 830 IP54 II KL. DALI OPAL (24W) 300MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	24	Impact resistance:	IK08
Index:	664250	Ingress protection:	IP54
Colour temperature [K]:	3000	Mounting version:	surface
Light source:	LED module	Dimensions of single box [mm]:	305/305/60
Luminous flux [lm]:	2100	Net weight [kg]:	0.950
Rated power of the luminaire [W]:	26	Warranty [years]:	5
Diffuser type:	OPAL	Category type:	bulkheads
Supply voltage [V]:	220-240	Category of application:	HoReCa, commercial facilities, educational institutions
Frequency [Hz]:	50 - 60	AC voltage range [V]:	220 - 240
DIMM DALI:	yes	LED lifespan L70B50 [h]:	120000
Colour of the body:	white	LED lifespan L80B20 [h]:	80000
Luminous efficacy [lm/W]:	85	LED lifespan L90B10 [h]:	40000
Energy efficiency class:	F	Light distribution type:	open space
Electrical protection class:	II	Power factor:	0.92
Colour rendering index:	>80	Working temperature [°C]:	from -20 to +35
Beam angle [°]:	120	Permeability factor of the diffuser:	0.70
Diffuser material:	PS	Version:	LENS
Diffuser colour:	white	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Optics material:	PMMA	Warranty [years]:	5
Optics:	lens	ENEC Certificate:	0316/ENEC/23
Material of the body:	ABS	CE certificate:	111/2023
Dimensions (H/W/T/S) [mm]:	300/300/58	PZH certificate:	B-BK-60212-0479/21
Mounting dimensions [mm]:	210	Manual:	Download PDF
		Plik LDT:	Download

LIGHT CURVES

