

REFLEX

WALL-MOUNTED INDIRECT LIGHT | 72CM

STH9741BR/27



20W

Power

1800lm

Luminous flux

110° / 110°


Beam angle



TECHNICAL SPECIFICATIONS TABLE

Beam angle	110° / 110°
Luminous efficacy	90lm/W
Power factor	0,92
Luminous flux	1800lm
Frequency	50/60Hz
Ingress protection rating (IP)	IP65
CRI (Color rendering index)	80
Power	20W
Correlated color temperature (CCT)	2700K
Voltage (V)	100-240V
Voltage (Vac)	100-240Vac
Lifespan	25000h


Technical Drawing



OTHER INFORMATION

Finishing	White
Color temperature	Warm white
Dimmable	No
Warranty	2 years
Patent information	Patented product
Prevailing material	Aluminum

Graphics



DOWNLOADS

[↓ IES FILE - STH9741BR/27](#)
[↓ MANUAL Reflex](#)
[↓ SKETCHUP - STELLA - STH9741BR-27-30 - STH9741PTO-27-30 - REFLEX - ARANDELA DE LUZ INDIRECTA 72cm_PACK.zip](#)
[↓ REVIT - STH9741BR_27_PTO_27_STH9741BR_30_PTO_30.rfa](#)
