

Anybus Wireless Bolt - Ethernet RJ45 PoE - Black version



Item number: **AWB2030-B**

The Anybus Wireless Bolt Ethernet RJ45 PoE - Black connects Ethernet-based machines to wireless networks via Bluetooth[®], Bluetooth Low Energy, or Wi-Fi. Designed for multi-directional applications, it's ideal for establishing wireless connections with roaming machines, such as AGVs or control cabinets from any angle. PoE support simplifies installation.

Enable wireless industrial communication via Bluetooth or Wi-Fi

Features and benefits

- ✓ **Low total cost of ownership**
Thanks to the integrated design of the antenna and communication module, there's no need for additional antenna or accessory purchases.
- ✓ **Designed for multi-directional applications**
Ideal for establishing wireless connections to roaming machines, such as AGVs, or to control cabinets from any angle.
- ✓ **Quick start up and high determinism**
Ideal for connecting field-level devices that require short start-up times and high determinism.
- ✓ **Supports Industrial Ethernet, TCP, & UDP protocols**
Communicates over Industrial Ethernet, supporting protocols such as BACnet/IP, PROFINET, EtherNet/IP, Modbus TCP, as well as all TCP and UDP-based protocols.
- ✓ **Easy to install**
Attach the Wireless Bolt directly onto cabinets or machines to look like an integrated part of the installation. Or use the Bolt Base Protector mounting kit to install it on a pole, wall, or similar.
- ✓ **Insights into your network**
The Command Line Interface (CLI) provides configuration and diagnostic capabilities, offering greater control and insight into your network.
- ✓ **High-speed, roaming, dual network bridging**
Provides fast roaming (IEEE 802.11r) and high link speeds (IEEE 802.11n). Simultaneous Bluetooth and Wireless LAN operation allows bridging between the two networks for enhanced connectivity.
- ✓ **Easy access to data**
Wirelessly connect to the Anybus Bolt and easily access the machine or cabinet. Configure the PLC or machine without halting or hindering production.
- ✓ **All-in-one wireless communication**
All-in-one package featuring a connector, communication processor, and integrated antenna in the same unit. Use a single cable for both power and communication with Power over Ethernet (PoE).
- ✓ **Industrial design**
Withstands harsh environments due to its IP66/67-rated enclosure and wide operating temperature range. Choose the white top Sunbolt option for 30% better protection against higher temperatures.
- ✓ **Easy to configure**
Establish a wireless connection in seconds thanks to the intuitive web-based interface.
- ✓ **Perfect together!**
Fully compatible with Anybus Wireless Bridge, a wireless product designed for point-to-point applications, enabling you to implement comprehensive wireless infrastructure.

Anybus Wireless Bolt - Ethernet RJ45 PoE - Black version



General

| | |
|------------------------------|--|
| Net Weight (g) | 85 |
| Net Dimensions (mm) | 68 x 75 (Ø X H) Height above mounting surface: 42. |
| Packed Width (mm) | 12 |
| Packed Height (mm) | 8 |
| Packed Depth (mm) | 12 |
| Packed Weight (g) | 185 |
| Operating Temperature °C Min | -40 |
| Operating Temperature °C Max | 65 |
| Storage Temperature °C Min | -40 |
| Storage Temperature °C Max | 85 |
| Power Consumption (W) | 1.7 |
| Input Voltage (V) | 19-36 |
| Power over Ethernet (PoE) | 37-57 V |
| Power Connector | 3-pole |
| Housing Materials | Plastic |
| Packaging Material | Cardboard |

Identification and Status

| | |
|-------------------|-----------|
| Product ID | AWB2030-B |
| Model Code | AWB2BA |
| Country of Origin | Sweden |

Anybus Wireless Bolt - Ethernet RJ45 PoE - Black version



Identification and Status

| | |
|---|------------|
| HS Code | 8517620000 |
| Export Control Classification Number (ECCN) | 5A992.c |

Physical Features

| | |
|-----------------------------|-------------------------------|
| Connectors / Input / Output | RJ45, 3-pole screw connection |
|-----------------------------|-------------------------------|

Wi-Fi Features

| | |
|--------------------------------------|---|
| Operation Mode | Access Point, Client |
| RF Output Power | 18 dBm EIRP (including antenna gain 3dBi) |
| Max No. Of Connections, Access Point | 7 |
| Security | WPA2 Personal; WPA2 Enterprise |

Bluetooth Features

| | |
|------------------------|------------------------|
| Operation Mode | Access Point, Client |
| Max No. Of Connections | 7 |
| Bluetooth Version | Classic Bluetooth v2.1 |

Bluetooth Low Energy Features

| | |
|-----------------------------|--|
| Operation Mode (LE) | Access Point, Client |
| RF Output Power (LE) | 14 dBm EIRP (including max antenna gain 3 dBi) |
| Max No. Of Connections (LE) | 7 |
| Bluetooth Version (LE) | Bluetooth v4.0 |

Certifications and Standards

| | |
|---------------------|---|
| Protection Class IP | IP66, IP67 |
| Vibration and Shock | Sinosoidal vibration test according to IEC 60068-2-6:2007 and with extra severities; Number of axes: 3 mutually perpendicular (X:Y:Z), Duration: 10 sweep cycles in each axes, Velocity: 1 oct/min, Mode: in operation, Frequency: 5-500 Hz, Displacement ± 3.5 mm, Acceleration: 2g. Shock test according to IEC 60068-2-27:2008 and with extra severities; Wave shape: half sine, Number of shocks: ± 3 in each axes, Mode: In operation, Axes $\pm X,Y,Z$, Acceleration: 30 m/s ² , Duration: 11 ms. |
| Environment | EN 61000-6-2:2019 EN 61000-4-2:2009 EN 61000-4-3:2006 + A1:2008 + A2:2010 EN 61000-4-4:2012 EN 61000-4-5:2014 EN 61000-4-6:2014 EN 61000-6-4:2019 |

