






Analogue signal converter 4-20mA/ output 4-20mA

| | |
|--|---|
| Series | CON |
| Code | XCONPC528P |
| Type | CON-PC-528P |
| HS code | 85043129 |
| INPUT TECHNICAL DATA | |
| Signal type IN | analogue |
| Input range IN | 4...20 mA |
| OUTPUT TECHNICAL DATA | |
| Signal type OUT | analogue |
| Output range OUT | 4...20 mA |
| Load impedance OUT | <1 K Ω (Rb) |
| Ripple | <5 mV |
| Status indication | LED |
| GENERAL TECHNICAL DATA | |
| Accuracy | 0.1% FSR (23°C) |
| Linearity error | <0.06% (100 Ω) |
| Temperature coefficient | <150 ppm / K FSR |
| Operating temperature range | -25...+60°C |
| Insulation | 1.5 kVac / 60 s |
| Insulation type | 2-way (IN-OUT) |
| Standard approvals | EN 60947-5-1 |
| Overvoltage category / pollution degree | II / 2 |
| Protection degree | IP 20 |
| Connection terminal IN / OUT | 2.5 mm ² / 2.5 mm ² (push-in) |
| Housing material | UL94V-0 plastic material |
| Dimensions (LxHxD) | 6.2x93x73 mm |
| Approximate weight | 40 g |
| Mounting information | on a rail, side by side |
| ACCESSORIES | |
| Mounting rail (IEC60715/TH35-7.5) | PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB |
| APPROVALS AND MARKINGS | CE,  |



* Input: 4...20 mA* Output: 4...20 mA* Insulation: 1.5 kVac, 2-way isolation* Suitable for loop powered sensors

DESCRIZIONE DEL PRODOTTO

CON-PC-528P
Analogue signal converter 4-20mA/ output 4-20mA