

WJP O B M (786 712)

- Reflectors in the torso and leg area to improve visibility
- Two-way zip



Figure without obligation

| Type | WJP O B M |
|-----------------------------------------------|--------------------------------------------------|
| Part No. | 786 712 <small>NEW</small> |
| High-pressure resistant | ≤ 750 bar |
| Size | 50 (M) |
| Material | multilayer laminate |
| Type | breathable and waterproof |
| Standards / test principles | EN 343, EN 13034 (type 6), GS-IFA-P15 (as basis) |
| Test parameters according to GS-IFA-P15 | flat jet nozzle type B |
| - Distance (nozzle – surface of test sample) | 7.5 cm |
| - Angle (high-pressure water jet) | 15 ° |
| - Speed (feed) | 0.5 m/s |
| - Quantity of water (high-pressure water jet) | 22 l/min |
| - Pressure (high-pressure water jet) | 900 bar* |
| Weight | 1.37 kg |
| Customs tariff number | 62113310 |
| GTIN | 4013364439047 |
| PU | 1 Stk |

*) The test against high-pressure water jet penetration is performed with a safety factor of 1.2.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.