

PRODUCT DATASHEET

ECO CLASS AREA 60 W 4000 K Gray

ECO CLASS AREALIGHTING Gen 2 | Streetlighting luminaires



Areas of application

- Road lighting
- Streets
- Car parks
- Area lighting

Product benefits

- Energy savings thanks to high system efficacy: up to 120 lm/W
- Low maintenance and operation costs due to long lifetime of LED
- 5 years guarantee

Product features

- Available with color temperature: 2,700 K, 3,000 K, 4,000 K, 6,500 K
- Lifetime (L70/B50): up to 50,000 h
- Type of protection: IP66
- Impact resistance: IK08
- Operating temperature range at t_a : -35...50 °C
- Robust die-cast aluminum housing
- Suitable for spigot diameter of 42 mm, 48 mm and 60 mm



TECHNICAL DATA

Electrical data

Nominal wattage	60.00 W
Nominal voltage	100...240 V
Mains frequency	50...60 Hz
Max. number of luminaires per miniature circuit breaker B16	16
Max. number of luminaires per miniature circuit breaker C10	15
Max. number of luminaires per miniature circuit breaker C16	24
Power factor λ	> 0.90
Protection class	I
Operating mode	Mains voltage

Photometrical data

Luminous flux	7200 lm
Luminous efficacy	120 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	≤ 5 sdc _m
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	135 ° x 75 °

Dimensions & Weight

Length	409.00 mm
Width	151.00 mm
Height	83.00 mm
Product weight	1519.00 g

Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Aluminum
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-30...+50 °C
Temperature range at storage	-35...+70 °C
Type of connection	Cable, 3-pole
Type of protection	IP66
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Suspended
Mounting location	Pole
Application environment	Outdoor
LED module replaceable	Not replaceable

Lifespan

Lifespan L70/B50 at 25 °C	50000 h ¹⁾
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / ROHS / REACH
-----------	-------------------

DOWNLOAD DATA

Documents and certificates



User instruction



Declarations Of Conformity CE

Photometric and lighting design files



IES file (IES)



LDT file (Eulumdat)

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075425491	Folding box 1	448 mm x 121 mm x 200 mm	1719.00 g	10.84 dm ³
4058075425507	Shipping box 8	507 mm x 467 mm x 422 mm	14560.00 g	99.92 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.