


FLAT SLIM square

312543.004.76 | Pendant luminaires



Pendant luminaires
4051859503125
L 430, B 430, H 72

pendant
silver, matt (approx. RAL 9006)



Decorative square LED pendant luminaire. Base: pressure die-cast aluminium, powder-coated. Standard Gore™ Protective Vents diaphragm valve to avoid condensation. Canopy made of aluminium, powder-coated. Diffuser: matt crystal glass, painted inside, with fixing device. Diffuser with frame made of pressure die-cast aluminium, powder coated, bonded. Diffuser attached with clip system. Homogeneous and smooth light distribution. Suitable for pendant. 4-point steel cable suspension, steplessly adjustable. Special lengths available on request. Transparent connecting cable. MultiLumen: 2 steps adjustable luminous flux. MultiColour: Colour temperature adjustable via jumper. Factory setting is 3000 K.

Product specifications

Length L	430 mm
Width B	430 mm
Height H	72 mm
Suspension length LP	500-1200 mm
Weight	10.704 kg
Light source	LED
Colour temperature	3000 K 4000 K
Rated luminous flux	3000 K: 4250 lm 2950 lm
	4000 K: 4550 lm 3150 lm
System power	3000 K: 42 W 29 W
	4000 K: 42 W 29 W
System efficiency	3000 K: 101 lm/W 102 lm/W
	4000 K: 108 lm/W 109 lm/W
Glare evaluation UGR (4H 8H)	3000 K: 22,8 21,6
	4000 K: 23,1 21,8
Beam angle	down 120° up 180°
Rated life	50000 h (L80/B10)
Colour rendering index (CRI)	80
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	12
Luminaires on B16A fuse	20
Luminaires on C10A fuse	21
Luminaires on C16A fuse	34
Inrush current / Inrush current duration	21 A / 230 µs
CIE Flux Code / CEN Flux Code	44 75 93 93 100
Type of protection	IP 40
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK07
Ambient temperature	-20 °C ... + 35 °C
Conformity mark	CE, EAC

FLAT SLIM square

312543.004.76 | Pendant luminaires



Spareparts

982676.014
Replacement glass